

9" Reflector LED Light Engine Trims (850-3000 lm)



Features

- Dimmable Triac/ELV or 0-10V.
- USA Designed and Assembled.
- Frame sold separately (see Compatible Housings).
- Meets the requirements for Title 24.
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	12.8W
Lumens	1250 lm
Color Temp.	4000K
Lamp Type	LED
Beam Angle	60°
CRI	93+
Wet Location	Listed

Options



Black



Chrome



Haze



Haze w/White Ring



White

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED technology.

Reflector Construction: Reflector is one piece, deep, self-flanged construction spun from .05" thick High Grade Aluminum. Reflector allows for minimal glare and a strong glare cut-off.

Installation: Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel and as a Retrofit Kit.

LED Technology:


- Extremely accurate Color Rendering Index of 93+ CRI.
- Efficacy of >90 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Listings:

- cULus Listed for Wet Location.
- RoHS Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions



Product Number Builder Example: E910L0827W2

ELCO 9" Reflector	Laurel	Lumens	Color Temp.	Finish
E910	L	08 850 lm	27 2700K	H All Haze

12 1250 lm
16 1600 lm
20 2000 lm
30 3000 lm

30 3000K
35 3500K
40 4000K
50 5000K
SD Sunset

W All White
B All Black
C All Chrome
HW Haze w/White Ring

Generation


Gen 1
2 Gen 2

LED Light Engine

Multiplier: 2700K (x 0.88), 3000K (x 0.92), 3500K (x 0.96)

PHOTOMETRIC REPORT

Product #: E910L2040
Wattage/Lumens: 23.2W/ 1850 Lm
Luminaire LPW: 80 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	2144
5	2146
15	1866
25	1388
35	702
45	55
55	0
65	0
75	0
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	134	4.7'
6'	59.6	7.0'
8'	33.5	9.3'
10'	21.4	11.7'

ZONAL LUMEN SUMMARY


Zone	Lumens	% Luminaire
0-30°	1361.91	73.60
0-40°	1789.01	96.70
0-60°	1850.2	100.00
0-90°	1850.23	100.00

Compatible Products

For use with 9" Laurel™ Light Engines



9" Laurel™ Commercial LED Frames



E9LT
9" Retrofit Kit

PRODUCT NUMBER BUILDER

Frame Type	Voltage	Lumen	Dimming	Optional	Generation
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
E9LT Retrofit	U 120/277V	08 850 lm 12 1250 lm 16 1600 lm 20 2000 lm 30 3000 lm 40 4000 lm 60 6000 lm	D Triac/ELV/0-10V S Sunset L Lutron	EM1 Emergency Backup up to 700 lm output EM2 Emergency Backup up to 1100 lm output	Gen 1 2 Gen 2