

Project name:	
Fixture type:	
Date:	

" Remodel Housing

3" remodel housing with a magnetic or electronic transformer designed for LED MR16 lamps. Uses a GU5.3 Bi-Pin socket for use with Bi-Pin LED MR16 lamps.



Features

- Single wall Airtight IC construction, for use in insulated
- Thermally protected magnetic transformer, 120V/12V/14W Magnetic AC.
- Lamp: MR16 GU/GX5.3 BiPin LED/Halogen (not included).
- Note: Use only dimmers specifically designed for used with magnetic transformer. Low voltage luminaires may produce audible sound when used with dimmers.

Specifications

Wattage	12W			
Voltage	120V			
Lamp Type	LED			
Wet Location	Listed with Shower Trims			
Damp Location Listed				

Options



Magnetic **Transformer**

Electronic Transformer

Technical Details

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x6 joists or taller are used. Maximum hole cutout is 3 3/4". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- · Output Voltage: 12V AC.
- · Max Wattage: 12W
- Magnetic or electronic transformer available. No minimum load.
- · Thermally protected against improper lamping.

Trims: Compatible with ELCO Low Voltage MR16 trims.

Dimmability:


- · Magnetic transformer dims with MLV type dimmers.
- · Electronic transformer dims with ELV type dimmers.
- · See dimming compatibility list for a list of compatible dimmers.
- · Note: Lamp used may affect dimmability.

Lamp: Designed for use with GU5.3 MR16 LED lamps.

Listinas:

- UL Listed for Damp Location.
- UL Listed for Wet Location with select trims.
- UL Listed for Feed Through.
- UL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Dimensions



1		131/	"
1		157.	2
((()_,		

Product Number

Item	Description	Lamp type	Watts	Voltage
EL2699LDRICA	3" Remodel Housing for 12V Bi-Pin MR16 LED with Magnetic Transformer	LED	12W	120V

Varranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a seriod of 3 years.	