


Project name:
Fixture type:
Date:

4" Square Reflector Trim



Features

- Square Reflector.
- Lamp: 32W MAX. CFL, 50W MAX PAR20 or R20.
- O.D.: 4 3/4" Square.


Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



Product Number

Item	Description	Finish
EL2999KW	with Socket Bracket	All White

Product Number Builder Example: EL2999W

Socket Bracket EL2999 W All White no Socket Bracket K with Socket Bracket B Black w/White Ring

C Clear w/White Ring CN Clear w/Nickel Ring

BZ All Bronze

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction



4" Airtight IC Housing New Construction

1	CAT NO.
100	EL99ICA

SPECI	FICAI	IONS	
amn.	50W	MΔΥ	

CAT NO.	SPECIFICATIONS	
EL99A	Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS	
FI 99I DICA	Lamp: LED 12W MAX.	



4" Airtight IC Housing Remodel



4" Housing Remodel



4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL99RICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
FI 99RA	Lamp: 50W MAX

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	



4" Airtight IC Housing with GU24 Base Socket New Construction



4" Airtight IC Housing with GU24 Base Socket Remodel

CAT NO.	SPECIFICATIONS
FI 99ICΔ-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
EL99RICA-G24	Lamp: 18W MAX.

4" Accessories

CAT NO.

FIRECVR



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.

\	
ש	

Fire Enclosure



C	CAT NO.	SPECIFICATIONS
F	FIREENCL	20 %" L x 14 %" W
F	FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRETAPE	³⁄4″ W × 16′ L	