

4" Round LED Reflector Insert

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others.



Features

- Fits ELCO 4" Dedicated LED Recessed Housings, Regular and Shallow.
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation.
- Deep set LED trim reduces glare while providing area illumination.
- Medium Base Adapter (PSA30) included.
- Energy Star Certified.
- Title 24 JA8-2019 Compliant.
- Life Span of 50,000 hours L70.

Specifications

| | |
|---------------------|-----------|
| Wattage | 11W |
| Lumens | 800 lm |
| Voltage | 120V |
| Color Temp. | 3500K |
| Dimmable | Triac/ELV |
| Lamp Type | LED |
| Beam Angle | 90° |
| CRI | 93+ |
| Wet Location | Listed |

Options



White



Bronze

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.

Construction: For use in IC and non-IC housings. Spun Aluminum for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Includes PSA30 medium base adapter for retrofitting existing housings. Quick connect for use with ELCO housings EL490ICA, EL490RICA, EL492ICA, EL492RICA, EL49FICA, EL49FICA. PSA30 (Medium Base Socket adapter) allows for use with EL99ICA, EL99RICA, EL99FICA, EL99A, EL99RA. PSA31 (GU10 Socket Adapter, not included) allows for use with EL49ICA, EL49A, EL49RA. PSA35 (GU24 Socket Adapter, not included) allows for use with EL99ICA-G24, EL99RICA-G24. Can be used in IC and non-IC housings.

Electrical: Driver connects to 120V power supply. High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.


LED Technology: Extremely accurate color rendering with 93+ CRI. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integral heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Industry leading dimming. Dims smoothly with no hot spots or flickering.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. Title 24 JA8-2019 Compliant

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Number

| Item | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Beam Angle | Finish |
|-----------|-----------|--------|-------|-------|---------|-----------|------------|--------|
| EL41535BZ | LED | 800 lm | 3500K | 11W | 120V | Triac/ELV | 90° | Bronze |

Product Number Builder Example: EL41527W

ELCO 4" LED Reflector Insert

Color Temp.

Finish

EL415

27 2700K

30 3000K

35 3500K

40 4000K (White Only)

50 5000K (White Only)

W White

BZ Bronze

Compatible Products

For use with 4" LED inserts

4" Dedicated LED ICA Housings



4" ICA Housing
New Construction



4" ICA Housing
Remodel




2-Hour Fire Rated 3" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|--------------|--|
| EL490ICA | |
| EL490ICA-7 | 277V |
| EL490ICA-EM5 | Emergency Battery Back-up (90 minutes) |

| CAT NO. | SPECIFICATIONS |
|-----------|----------------|
| EL490RICA | 5 1/2" Height |

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------------|
| EL49FICA | 7 1/2" Height - Sound Rated |
| EL49FICA-7 | 277V |

4" Shallow Dedicated LED IC Housings



4" LED Shallow Housing
New Construction




4" LED Shallow Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|------------|------------------------|
| EL492ICA | 14W MAX. 3 1/2" Height |
| EL492ICA-7 | 277V |

| CAT NO. | SPECIFICATIONS |
|-----------|------------------------|
| EL492RICA | 14W MAX. 3 1/2" Height |

4" Accessories



Emergency Battery Backup



Fire Cover



Fire Enclosure

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 8W, 120/277V |

| CAT NO. | SPECIFICATIONS |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |

| CAT NO. | SPECIFICATIONS |
|------------|----------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 3/8" W |



Mica Fire Tape



Socket Adapter



Socket Adapter

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |

| CAT NO. | SPECIFICATIONS |
|---------|-----------------------|
| PSA30 | Medium Base Connector |


| CAT NO. | SPECIFICATIONS |
|---------|----------------------------------|
| PSA31 | GU10 to ideal terminal connector |

LED Reflector Insert

Multiplier: 2700K (x 0.96), 3500K (x 1.04), 4000K (x 1.08), 5000K (x 1.12)

PHOTOMETRIC REPORT

Product #: EL41530
 Wattage/Lumens: 10.2W/ 725 Lm
 Luminaire LPW: 71 Lm/W



CANDLE POWER SUMMARY

| Degrees Vertical | 0° |
|------------------|------|
| 0 | 290 |
| 5 | 287 |
| 15 | 273 |
| 25 | 249 |
| 35 | 212 |
| 45 | 167 |
| 55 | 117 |
| 65 | 66 |
| 75 | 20 |
| 85 | 2.04 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Footcandles Beam Center | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 18.1 | 10.1' |
| 6' | 8.06 | 15.2' |
| 8' | 4.53 | 20.3' |
| 10' | 2.90 | 25.4' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|-------|--------|-------------|
| 0-30° | 223.37 | 30.80 |
| 0-40° | 361.81 | 49.90 |
| 0-60° | 613.63 | 84.60 |
| 0-90° | 725.45 | 100 |