

# 4" Square Baffle Trim



## Features

- Square Baffle.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- 4 3/4" Square.

## Technical Details

### Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Diecast trim ring for durability and lasting quality.
- Baffle helps reduce glare.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



All White



Black w/White Ring

## Product Number

Item	Finish
EL991B	Black w/White Ring

## Product Number Builder Example: EL991W

4" Square Baffle Trim	Finish
EL991	W

**W** All White  
**B** Black w/White Ring

# Compatible Products

For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.




4" Airtight IC Housing  
Remodel

CAT NO.	SPECIFICATIONS
EL99RICA	Lamp: 50W MAX.




4" Housing  
Remodel

CAT NO.	SPECIFICATIONS
EL99RA	Lamp: 50W MAX.




4" Airtight IC 2-Hour Fire Rated Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.



4" Airtight IC Housing with GU24 Base Socket  
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC Housing with GU24 Base Socket  
Remodel

CAT NO.	SPECIFICATIONS
EL99RICA-G24	Lamp: 18W MAX.

## 4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L