

Project name:	
Fixture type:	
Date:	

6" Super Sloped Ceiling Medium Base Non-IC New Construction Housing

ELCO Slant allows for installation in sloped ceilings ranging from 7/12 (30°) to 12/12 (45°). Fits in $2" \times 8"$ joist construction.



Features

- Non-IC Super Slope New Construction Housing.
- Integral thermal protector guards against improper lamping.
- Designed for use in 7/12 to 12/12 sloped ceiling.
- Socket: Medium base E26.
- Compatible with Medium Base Incandescent, CFL or LED Lamp MAX. 90W. Works with LED Quick-Connect Inserts with PSA30 Socket Adapter.

Specifications

Wattage	85 or 90W			
Voltage	120V			
Lamp Type	Medium Base (E26)			
Damp Location Listed				

Technical Details

Construction:

- Designed for use in 7/12 to 12/12 sloped ceiling where insulation must be kept 3" away from fixture housing.
- $\bullet~$ Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Aluminum housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. High strength hanger bars can easily be nailed to joists. Template for hole cutout is provided with each housing. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and four pry-out knockout slots for easy romex installation.

Hanger Bars: Pre-installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

Electrical:


- Rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

Trims: Compatible with EL602, EL603, EL604, EL606, EL607, EL608.

Listings: UL Listed for Damp Location.

UL Listed for Feed Through.

Dimensions



Product Numbers

Item	Lamp type	Watts	Voltage
EL901HT	Medium Base (E26)	85 or 90W	120V