

Project name:		
Fixture type:		
Date:		

4" Reflector Trim with Socket Bracket



Features

- Reflector Trim.
- Integral Socket Bracket to control lamp height.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- Q.D.: 5'

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







All White

Black/White Ring

Clear/White Ring



Gold/White Ring

Dimensions



Product Number

Item	Finish
EL999KB	Black/White Ring

Product Number Builder Example: EL999KW

4" Reflector Trim Finish

EL999K

W All White

- B Black/White Ring
- C Clear/White Ring
- **G** Gold/White Ring

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing
New Construction



4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing Remodel

FO:0 #	7	
(3)	R	8
	44	0 1

4" Housing Remodel



4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99RICA	Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS
EL99RA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

000	7	1
	to	2
	//1	d d
	1	

4" Airtight IC Housing with GU24 Base Socket Remodel

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
FI 99RICΔ-G24	Lamp: 18W MAX.

4" Accessories

CAT NO. FIRECVR



Fire Cover	

9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 %" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRETAPE	³ ⁄4" W × 16' L	