

5" Low Voltage Remodel Housing




Features

- Remodel Housing.
- Versatile, reliable and easy to install.
- Unit slips through 5 1/2" ceiling cut out.
- Integral flange secures fixture against ceiling.
- Four remodel clips secure housing and accommodate various ceiling thickness.
- Junction box listed for 90° supply wire.
- Lamp: 12V, MR16 GU/GX5.3 bi-pin LED (not included).
- Lamp Holder: MR16 GU/GX5.3 bi-pin socket.
- Trims sold separately.

Specifications

| | |
|----------------------|-------------|
| Wattage | 75W |
| Voltage | 120V |
| Lamp Type | GU5.3 BiPin |
| Damp Location | Listed |

Dimensions



Technical Details

Construction:

- Remodel housing with thermal protector.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Steel housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller joists are used. Maximum hole cutout is 5 1/2". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- Output Voltage: 12V AC.
- Thermally protected against improper lamping.

Trims: Compatible with ELCO 5" MR16 trims.

Dimmability:

- Magnetic transformer dims with MLV type dimmers.
- See dimming compatibility list for a full list of compatible dimmers.
- Note: Lamp used may affect dimmability.

Lamp: Designed for use with GU5.3 MR16 LED lamps.

Listings:

- UL Listed for Damp Location.
- UL Listed for Wet Location with select trims.
- UL Listed for Feed Through.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

Product Numbers

| Item | Lamp type | Watts | Voltage |
|--------|-------------|-------|---------|
| EL5RLV | GU5.3 BiPin | 75W | 120V |