



#### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on left and right side with diffuser for a finished side view
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- 7-year limited warranty
- Patent: [www.electricmirror.com/patents](http://www.electricmirror.com/patents)
- Made in America with U.S. and global components

#### AVAILABLE OPTIONS

- Defogger
- Custom sizes

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 60 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L<sub>70</sub> 52,000-hour LED lifespan

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

#### PRODUCT DESCRIPTION

A singularly smart and modern alternative to bathroom sconces, Novo™ pairs incredible natural-looking illumination with ultra-soft wall glow, forming a harmonious combination of task and ambiance lighting.

#### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as left and right-side wall-glow ambient lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with a greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 7-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

**MODELS**

Base Model*	Dimensions	Initial Lumens/Fixture	Power Requirements
NOV-2436	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	3,960	120/240 VAC, 52W
NOV-3636	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	3,960	120/240 VAC, 52W
NOV-4836	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	3,960	120/240 VAC, 52W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [residential@electricmirror.com](mailto:residential@electricmirror.com).

**DIMENSIONAL DRAWING** (Not to scale. Frost and border widths may vary depending on mirror size.)

