


# VPT464K



## 46" LED Vapor Tight Fixture

46"Lx4.75"Wx4.25"H LED Vapor Fixture  
 52W, producing over 4600 fixture lumens  
 LED module is designed to provide 50,000 hours of life.



LED Vapor Tight

VPT464K



### Performance

- PC base & lens
- With LM-80 LED chips
- ETL and cETL listed, DLC Listed.
- Dimmable

### Construction

- PC base & lens
- 2xQT2600/720/2FT LED Modules
- One LED DRIVER

### Installation

- The LED vapor tight fixture is surface mounted by standard mounting screw (mounting screws not provided)



### Photometric

#### 3.2 Photometric data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Total Lumens	-	-
Luminaire Efficacy	-	-
Correlated Color Temperature (CCT)	5279 K	-
Color Rendering Index (CRI)	84.2	-
R9	17	-
Chromaticity Coordinate (x,y)	x= 0.3379 y= 0.3495	-
Chromaticity Coordinate (u,v)	u= 0.2074 v= 0.3217	-
Chromaticity Coordinate (u',v')	u'= 0.2074 v'=0.4826	-
Duv	0.0019	-
Spacing Criteria (0-180)	-	-
Spacing Criteria (90-270)	-	-

#### 3.2 Photometric data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Total Lumens	-	4603.67 lm
Lumens per Foot	-	1189.33 lm/ft
Luminaire Efficacy	-	89.57 lm/W
Correlated Color Temperature (CCT)	3089 K	-
Color Rendering Index (CRI)	81.0	-
R9	2	-
Chromaticity Coordinate (x,y)	x= 0.4292 y= 0.3961	-
Chromaticity Coordinate (u,v)	u= 0.2490 v= 0.3445	-
Chromaticity Coordinate (u',v')	u'= 0.2490 v'= 0.5170	-
Duv	-0.0021	-
7mm Lumens between 0-90°	-	85.5%

### Specifications

Model #	VPT464K
Input Voltage	120~277V AC, 60Hz
Color Temperature	4000K
CRI	80+
Current	110mA
Watts	52W
Lumens	4600LM
Dimmable	YES
Housing Material	PC
Lens	PC
Rating	ETL&cETL, DLC Listed, Damp locations
Dimensions	46"Lx4.75"Wx4.25"H
Power Factor	>95%
Mounting	Surface mount
LED Type	LM80 LEDs
Average Life (Hrs)	50,000 hrs.
Warranty	5-year limited