

Collection: Histoire

Installation manual for: LD4017D48 L47.4"W7.3"H7.1"L5

Installation instructions:

- 1. Using the screw (P7) secure the mounting bracket (P4) to the junction box.
- 2.According the mounting bracket (P1) to punching two holes in wall and put the expanded colloid (P5) in holes. Secure the mounting bracket (P1) by tapping screw(P6).
- 3. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 4. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 5. "E" wire from the fixture is attached to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 6.M5 screw (P3)pass through the holes in canopy plate and tighten by nut (P10).
- 7.Install the metal pipe (P12) to the wire lock (P13).
- 8.Install the lampshade (P16) and tighten by lamp holder ring (P17).
- 9.Install the bulb(not included) in lamp holder (P15).

The end!

PI P2 P3 P4 P7 P8 P9 P10 P11 P12 P13 P14 P15 P16 P17

PARTS LIST

part	picture	Description	Qty	Check list
P1	<u>e= ==</u>	L32.7″ Mounting bracket	1	
P2		M5 Nut	2	
Р3	—	M5 Screw	2	
P4		Ø 4.0″ Mounting bracket	1	
P5		Expanded colloid	2	
P6		Tapping screw	2	
P7	-	5/32-32 Screw	2	
P8		L41.9"Canopy plat	1	
Р9		0 0.7"Wire lock	5	
P10		Nut	2	
P11		Power Cord 6.5' 18# Black	5	
P12		L5.9"Metal pipe	5	
P13	Д	ø 0.8″Wire lock	5	
P14		Lamp cup	5	
P15		E26 Lamp holder	5	
P16		7.3"Lampshade	5	
P17		E26 Lamp holder ring	5	

"L" = Hot wire

"N" = Neutral wire

 $^{\prime\prime}$ E $^{\prime\prime}$ = Ground wire