

Collection:Script Installation manual for:

LD2351BK / LD2351BR / LD2351C / LD2351SG L19. 1"W19. 1"H5. 1"L8

Installation instructions:

1.Secure Mounting bracket(P1) to the junction box.

2.Insert screws(P2) in side of top unit the mounting bracket.

3.Black wire from ceiling(junction box) attaches to "L"wire from the fixture.

- 4. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 5. "E" wire from the fixture is attaced to the mounting bracket and an additional

"E" wire from the mounting bracket must be secured to the junction box. 6.Fix the Canopy(P3) to the Mounting bracket(P1) and tighten by the screws(P4). 7.Install the bulbs(bulbs not included) into the lampholder(P6).

The end!



1			
picture	Description	Qty	Check list
	L4.5″ Mounting bracket	1	
(prozessores	5/32-32 Screw	2	
	L4.7"W4.7"H1" Metal Canopy	1	
(IIII)	M4 Screw	2	
ŧ Ū Ū Ū	Metal Rod	4	
	E12 Metal Cup	8	
	ø11.8" Metal Cover	4	
	() () () () () () () () () () () () () (L4. 5" Mounting bracket Image: Solution of the second se	L4. 5" Mounting bracket 1 Image: Solution of the second