


Collection: Taryin Installation manual for:


LD7319W5SG W4.7"\*E5.8" H11.3" L1

## Installation instructions:

- 1. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4. Secure mounting bracket to the junction box.
- 5.Install the lamp body to the mounting bracket by screws(P3).
- 6.Locking the glass shade(P12) on the lamp body by socket rings(P9).
- 7.Install E26 light source.(Bulbs not supplied).

The end!





| Part Number    | Part | Picture   | Description                  | Qty |
|----------------|------|-----------|------------------------------|-----|
| MB7S05         | P1   | 0         | Mounting bracket L4.5"*W4.5" | 1   |
|                | P2   |           | Mounting bracket screw       | 2   |
| P-LD7319W5SG-1 | Р3   | 1         | Screw                        | 4   |
|                | P4   |           | Backplate (L4.7"*W4.7")      | 1   |
|                | P5   |           | Lamp arm(W3.6"*H4.1")        | 1   |
|                | P6   |           | Socket Cup (Φ2.2"*H0.8")     | 1   |
|                | P7   |           | Socket Cup (Φ4.5"*H1")       | 1   |
|                | P8   |           | E26 holder                   | 1   |
|                | P9   |           | Socket rings                 | 1   |
|                | P10  |           | UL18#Ground wire,L9.8"       | 1   |
|                | P11  | $\approx$ | UL18#,L8"                    | 1   |
| GS7R13         | P12  |           | Glass shade<br>(Φ4.3"*H6.3") | 1   |

<sup>&</sup>quot;L" = Hot wire "N" = Neutral wire "E" = Ground wire