

Explore Single Handle Bar/Prep Faucet Model LKEC1042 & LKLFEC1042

FEATURES

Model LKEC1042

- Pull-out spray with aerated flow and spray function
- 1-3/8" (35mm) diameter faucet hole required
- Maximum countertop thickness: 3" (76mm)
- Solid brass construction
- Removable ceramic disc cartridge
- 110° swing spout
- Flexible supply hose with 3/8" compression nut
- Ship weight is 8.8 lbs (4.0 kg)
- Available in the following finishes:
 - Chrome LKEC1042CR, LKLFEC1042CR
 - Brushed nickel LKEC1042NK, LKLFEC1042NK
 - Oil rubbed bronze LKEC1042RB, LKLFEC1042RB
 - Polished nickel LKEC1042PN, LKLFEC1042PN
- Maximum flow rate
 - 2.2 GPM/8.3 L/min at 60 PSI (LKEC1042)

Model LKLFEC1042

- Same as LKEC1042
- Maximum flow rate
 - 1.5 GPM/5.7 L/min at 60 PSI

WARRANTY

- Limited Lifetime

COMPLIES WITH:

- ADA
- ANSI/NSF61
 - Only LKEC1042 Model, Certified
- ASME/ANSI A112.18.1
- CA AB1953 ; VT S-152
- cUPC
 - Only LKEC1042 Model, Certified

