

PRODUCT SPECIFICATIONS

WaterSentry® Vandal-Resistant 5 micron Sediment Pre-filter Filtration Kit. Overall dimensions are 8-1/8" x 5-1/2" x 14-1/8".

| Dimensions: | 8-1/8" x 5-1/2" x 14-1/8" |
|------------------------|---------------------------|
| Shipping Weight: | 6 lbs. |
| Flow Rate: | 1.5 GPM (5.6 L/m) |
| Temperature: | 40-100°F (4-38°C) |
| Initial Pressure Drop: | 2-5 PSI (14-34 kPa) |
| Maximum Pressure: | 105 PSI (724 kPa) |
| Minimum Pressure: | 20 PSI (138 kPa) |
| Water Inlet: | 3/8" (9.5mm) O.D. tube |
| Water Outlet: | 1/4" (6.4mm) O.D. tube |

- Kit includes prefilter, mounting bracket, VR box, and tubing and connections for installation.
- Vandal-resistant box, made from 20-gauge powder-coated metal, protects filter and discourages tampering.
- Versatile mounting near accessible water line; box includes conduit punchouts on back and bottom and an open back for thru-wall plumbing; vandal-resistant conduit not provided.
- Universal box converts any non-filtered cooler, fountain or bottle filler into a filtered unit.
- Prefilter reduces dirt, sand and other sediment from water, improving taste and appearance and extending the life of downstream filters.
- Prefilter is tested and certified to NSF/ANSI 42 and 372 for material safety and structural integrity.
- 75-gram average weight dirt holding capacity for sediment reduction.
- For best results, replace prefilter every six months or as needed, depending on water quality.
- Universal prefilter can be paired with any existing Elkay or non-Elkay water filter to create a two-stage filtration system, preventing clogging of the main filter and reducing particulates in the water.
- Encapsulated filter cartridge allows for clean and sanitary filter changes.



A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



| PART: | QTY: |
|----------|------|
| PROJECT: | |
| | |
| DATE: | |
| NOTES: | |
| | |

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.