SPECIFICATIONS

GENERAL

#14 gauge, type 304 (18-8) stainless steel multiple station urinal. Welded seamless 1/4" (6mm) radii coved corner construction. Full length sloping backsplash. 1-1/2" (38mm) wide sloping top channel rim with 2" (51mm) flat front apron. Slanted front. Exposed surfaces polished to a satin finish. Bottom and back are sound deadened. Furnished with a continuous length wall hanger, integral stainless steel mounting "Z" brackets, and continuous flush pipe and drain.

(CHECK MODEL SPECIFIED)

□ EU4814C

□ EU6014C

FURNISHED COMPLETE WITH:

SUPPLY FOR EU4814C:	LK388. Chrome plated brass con- tinuous flush pipe, 3/4" (19mm) O.D. tubing. With flush pipe holders.
SUPPLY FOR EU6014C:	LK392. Chrome plated brass con- tinuous flush pipe, 3/4" (19mm) O.D. tubing. With flush pipe holders.

DRAIN: LK177. Chrome plated beehive strainer, 1-1/2" (38mm) O.D. tailpiece.

FOLLOWING MODELS DO NOT INCLUDE SUPPLY AND DRAIN FITTINGS:


□ EU4814

EU6014

URINAL IS PRE-DRILLED FOR PIPE HOLDERS AND DRAIN.

DIMENSIONS

Model		A		В		C		D		E		F		G		Н		I		J		К	
Numb		in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
EU4814	L I	48	1219	14	356	24	610	5 ¹ /2	140	8	203	22 ¹ / ₂	572	4 ¹ /8	105	4	102	10	254	3	76	12	305
EU6 14	L I	60	1524	14	356	30	762	5 ¹ /2	140	8	203	281/2	724	4 1/8	105	4	102	10	254	3	76	12	305




Elkay Manufacturing Company

www.elkay.com

2222 Camden Court Oak Brook, IL 60523

Printed in U.S.A. ©2001 Elkay Mfg. Co. (Rev. 5/01) 3-22C





EU6014 (7 HOLES)