Recreate the elegant look of marble and stone and add a touch of elegance and natural beauty to any space.





POOL

INDOØR





RESIDENTIAL

Alps

Vadret

FLOOR / WALL

Sizes	24 ["] x24" 23.62"x23.62"	12"×24" n.61"×23.62"	3 [°] x12″ Floor SBN					
Thickness	8.2mm	8.2mm	9mm					 Product and Installation Details ANSI A108.02 Section 4.3.8.2 - For running bond/brick joing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.
Faces	6	20	N/A					
Finish	Polished	Polished	Polished					
Edge	Rectified	Rectified C	Cut/Rounded					
Grout Joint Recommendation	3/16"	3/16"	3/16"					
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A137.1	Scratch Hardness MOHS	Shade Variation Rating	approve mock up and nppage.
Results*	111	>350 lbf	Resistant	<0.50%	<0.42	3	V2	Recommended 33% Offset*

Sustainability Attributes

Red List Free
 VOC

Health Product Declaration (HPD) provided

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.