


Denver UL Mortise Entryset  
Part # UL 3323



Standard interior trim  
Part # UL 3323\*

Additional Dimensions: (Part # UL 3323)

- Exterior Projection is 3"
- Interior Projection Depends on Handle Style
- Overall Grip thickness: 1"
- Clearance between door & grip is 1 1/2"
- Plates thickness: 1/2"

**Same dimensions for dummy function**

**\* Available in Lever By Lever/ Knob by Knob Mortise Entrance Handlesets. Same dimensions as interior trim of standard mortise entrance handlesets.**



| Door Thickness Specifications   |  |  |
|---|--|--|
| <p><b>Standard Door Thickness: 1 3/4"</b></p> <p>Standard Components:</p> <ul style="list-style-type: none"> <li>• 1 3/8" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2" Top Rosette Screw</li> <li>• 1 1/2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul> | <p><b>Extended Door Thickness: 1 7/8" - 2 1/4"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1 1/2" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2 1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul> | <p><b>Extended Door Thickness: 2 3/8" - 2 5/8"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1 3/4" Threaded Cylinder</li> <li>• 2 1/4" Long Spindle</li> <li>• 2 1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Extended Thumbpress</li> <li>• Extended Strikeplate</li> </ul> <p><b>• 2 3/4" TD Requires 2" Threaded Cylinder</b></p> |