



Rectangular Sectional UL Mortise
Part # UL 3324

Rectangular Monolithic UL Mortise
Part # UL 3325

Standard interior trim
Part # UL 3324/3325*

Additional Dimensions: (Part # UL 3324 & 3325)

- Exterior Projection is 3 1/8"
- Interior Projection Depends on Handle Style
- Overall Grip thickness: 1 3/4"
- Clearance between door & grip is 1 3/4"
- Plates thickness: 1/2"

Same dimensions for dummy function

*** Available in Lever By Lever/ Knob by Knob Mortise Entrance Handlesets. Same dimensions as interior trim of standard mortise entrance handlesets.**



| Door Thickness Specifications | | |
|---|--|--|
| <p>Standard Door Thickness: 1 3/4"</p> <p>Standard Components:</p> <ul style="list-style-type: none"> • 1 1/2" Threaded Cylinder • 2" Long Spindle • 2" Top Rosette Screw • 1 1/2" Bottom Rosette Screw • Thumbpress • Strikeplate | <p>Extended Door Thickness: 1 7/8" - 2 1/4"</p> <p>Extended Components:</p> <ul style="list-style-type: none"> • 1 1/2" Threaded Cylinder • 2" Long Spindle • 2 1/2" Top Rosette Screw • 2" Bottom Rosette Screw • Thumbpress • Strikeplate | <p>Extended Door Thickness: 2 3/8" - 2 5/8"</p> <p>Extended Components:</p> <ul style="list-style-type: none"> • 1 3/4" Threaded Cylinder • 2 1/4" Long Spindle • 2 1/2" Top Rosette Screw • 2" Bottom Rosette Screw • Extended Thumbpress • Extended Strikeplate <p>• 2 3/4" TD Requires 2" Threaded Cylinder</p> |