

FINISHES OPTION



GLASS Clear Ribbed 144

MATERIAL Steel, Aluminum, Glass

RATINGS CETLUS

Dry Location



ADDITIONAL RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

: 2.25" L x 2.25" W x 17" H

: 4.75" W x 0.25" H x 4.75" L

: 1 x 5W LED PCB Integrated , 5W Total

: 137" OAH

: 400 Rated (240 Del.)

: 2.2 lb

: (Integrated)

: Universal 3-in-1

: 120-277V

: 90 CRI : 3000K

Reeded glass tubes are paired with ribbed aluminum LED housings in your choice of Gold or Matte Black finishes. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light

sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to

MEASUREMENTS DIMENSION

HANGING WEIGHT

BULB INCLUDED

DIMMABLE

COLOR_TEMP

CRI

MAX OAH

CANOPY

LAMPING INPUT VOLTAGE

LUMENS BULB

be used in both residential and decorative commercial or hospitality applications. ADA compliant sconces are a welcome companion to the series as well as the fully metal stem hung pendant option designed without glass



PRODUCT DESCRIPTION

15"

2.25

*max overall height

140" Max OAH

and uses a JA8 Listed LED GU10 lamp instead of dedicated LED.

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com