

| Product Specifications for E20349-48 |           |  |  |
|--------------------------------------|-----------|--|--|
| Job Name:                            | Job Type: |  |  |
|                                      |           |  |  |
|                                      |           |  |  |
| Quantity:                            | Comments  |  |  |
|                                      |           |  |  |

N/A N/A N/A N/A N/A N/A N/A N/A N/A



E20349-48 Gala 3-Light Pendant

Finish Glass/Shade Product Category
Confetti

| Lamping<br>Number of Bulb(s) | 3               | <i>Measurements</i><br>Width |
|------------------------------|-----------------|------------------------------|
| Light Type                   | Incandescent    | Height                       |
| Bulb Type                    | MB              | Length                       |
| Max Bulb Wattage             | 75              | Extension                    |
| Max Fixture Wattage          | 225             | Back Plate Width             |
| Rated Life                   | ±2,500 Hours    | Back Plate Height            |
| Rated Lumens                 | ±2,400          | HCO                          |
| Color Temp                   | ±2,700 K        | Min Overall Height           |
| Bulb(s) Included             | No              | Max Overall Height           |
| Light Up/Down                | N/A             | Hanging Weight               |
| Beam Spread                  | N/A             | Height Adjustable            |
| CRI                          | N/A             | Slope                        |
| Photo Cell Included          | N/A             | Chain Length                 |
| Ballast/Driver/Transformer   | No              | Wire Length                  |
| Dimmable                     | Standard Dimmer | Canopy Width                 |
|                              |                 |                              |

| Measurements       |         | Shipping           |
|--------------------|---------|--------------------|
| Width              | 24.00"  | Carton Weight      |
| Height             | 13.00"  | Carton Width       |
| Length             | N/A     | Carton Height      |
| Extension          | N/A     | Carton Length      |
| Back Plate Width   | N/A     | Carton Cubic Feet  |
| Back Plate Height  | N/A     | Master Pack        |
| HCO                | N/A     | Master Pack Weight |
| Min Overall Height | N/A     | Master Pack Width  |
| Max Overall Height | 130.00" | Master Pack Height |
| Hanging Weight     | N/A     | Master Pack Length |
| Height Adjustable  | Yes     | Master Cubic Feet  |
| Slope              | N/A     | UPS Shippable      |
| Chain Length       | N/A     |                    |
| Wire Length        | N/A     |                    |
| Canopy Width       | N/A     |                    |
| Canopy Height      | N/A     |                    |
| Canopy Length      | N/A     |                    |

| Certification | Other | Equivalents |
|---------------|-------|-------------|
|               |       | _4          |

|               |     |          |              | The state of the s |     |
|---------------|-----|----------|--------------|--|-----|
| Safety Rating | DRY | UPC Code | 845094005643 | Incandescent Watts   | N/A |
| Energy Star   | No  | Material | N/A          | Fluorescent Watts  | N/A |
| CA Title 24   | No  |          |              |  |     |
| CA Title 20   | No  |          |              |  |     |
| ADA           | No  |          |              |  |     |

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.