

Р	Product Specifications for E94903-10SN			
	Job Name:	Job Type:		
	Quantity:	Comments		



## E94903-10SN

Minx 4-Light RapidJack Pendant and Canopy

**Finish** Glass/Shade **Product Category** Snow White Satin Nickel

Lamping	
Number of Bulb(s)	4
Light Type	Xenon
Bulb Type	12V G4
Max Bulb Wattage	20
Max Fixture Wattage	80
Rated Life	±2,000 Hours
Rated Lumens	±1,280
Color Temp	±2,900 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Low-Voltage

**ADA** 

Measurements	
Width	4.25"
Height	3.25"
Length	34.25"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	125.50"
Hanging Weight	N/A
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	63.00"
Canopy Width	4.5"
Canopy Height	2.3"
Canopy Length	34.5"

	Shipping	
5"	Carton Weight	N/A
5" 5"	Carton Width	7.00"
5"	Carton Height	8.50"
Α	Carton Length	7.00"
Α	Carton Cubic Feet	N/A
A A	Master Pack	1
Α	Master Pack Weight	N/A
A )"	Master Pack Width	N/A
)"	Master Pack Height	N/A
Α	Master Pack Length	N/A
s	Master Cubic Feet	N/A
Α	UPS Shippable	Yes
Α		
A )" 5"		
5"		

Certification		Other		Equivalents
Safety Rating	Dry	UPC Code	845094044437	Incandescent
Energy Star	No	Material	N/A	Fluorescent \

No

Safety Rating	Dry UPC Code	845094044437	Incandescent Watts	N/A
Energy Star	No <b>Material</b>	N/A	Fluorescent Watts	N/A
CA Title 24	No			
CA Title 20	No			

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.