INFLUENCERTM

FP3075** 22" Ceiling Fan



INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

79.5 x 64 AC motor is designed for optimal performance with this fan.

CONTROL OPTIONS:

TR500 hand-held remote control is included. Push button remote control with variable fan speeds, infinite light levels and off button. Optional WC2WH and WR501WH wall controls, BTCR9 hand held remote control, BTR9 receiver unit and WFR50 WiFi receiver unit are available — sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Six 4-watt dimmable LED bulbs included.

DOWNROD OPTIONS:

Fan comes with a 1" Dia. x 4.5" downrod (DR1-45). Optional downrods are available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 20°. Most sloped ceiling installations require a standard 4.5" downrod or longer downrod. Optional sloped ceiling kits (SCK1-52) are available for slope an angles up to 42°. Call technical support for more information.

LOCATION USE:

Fan is rated for dry locations. This fan is for rooms up to 100 sq ft.



	Α	В
Fan w/4.5" downrod	18.89″	13.50″
Fan w/12" downrod	26.39″	21.00″
Fan w/18" downrod	32.39″	27.00″
Fan w/24" downrod	38.39″	33.00″
Fan w/36" downrod	50.39″	45.00″
Fan w/48" downrod	62.39″	57.00″
Fan w/60" downrod	74.39″	69.00″
Fan w/72" downrod	86.39″	81.00″

Available Finishes				
BL	Black with Clear Blade			
BS	Brushed Satin Brass with Clear Blade			
СН	Chrome with Clear Blade			

Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	1215	1445	40	0.30	36
Med	652	1110	42	0.27	26
Low	653	792	52	0.21	15

Energy Guide FTC				
Power (W _{ave}) Total Air Delivery (CFM _{ave})		Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)	
27	1139	8	42	

Light Bulb Information (120V)					
Bulb Type Watts QTY Lumens Amo		Lumens Amount	Color Temp	CRI	
LED	4	6	2100	3000	90%