


AIR SHADOW™ SERIES

FP820** Mechanical Ceiling Fan Assembly



INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

188 x 18 motor is designed for optimal performance with this fan.

BLADES:

A set of four maple or cherry finish wood blades included.

CONTROL OPTIONS:

TR28 hand-held remote control with wall mount is included. Push button remote control has 3 fan speeds, infinite light levels, demo mode, reverse and off button. Instructions are provided with each control.

LIGHTING OPTIONS:

Fan is downlight adaptable. Optional lighting fitters and light kits are available—see our catalog or visit www.fanimation.com.

DOWNROD OPTIONS:

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods are available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 30° and up to 52°. Optional close-to-ceiling kit is available as well-sold separately. Call technical support for more information.

LOCATION USE:

Fan is rated for dry locations only.

	A	B
Fan w/6" downrod	17.50"	10.90"
Fan w/12" downrod	23.50"	16.90"
Fan w/18" downrod	29.50"	22.90"
Fan w/24" downrod	35.50"	28.90"
Fan w/36" downrod	47.50"	40.90"
Fan w/48" downrod	59.50"	52.90"
Fan w/60" downrod	71.50"	64.90"
Fan w/72" downrod	83.50"	76.90"

Available Finishes	
CH	Chrome with maple wood blades
PW	Pewter with cherry wood blades

Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	267	4514	87	0.40	48
Med	220	3696	103	0.38	35
Low	168	2776	127	0.33	22