

Warming Drawer, 30"

Series 9 | professional

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook. Pair with a Professional-style oven for design cohesion.

- A companion product, designed to match with other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

| | |
|--------|------------------------------------|
| Height | 10 ¹¹ / ₁₆ " |
| Width | 29 ¹⁵ / ₁₆ " |
| Depth | 22 ³ / ₈ " |

FEATURES & BENEFITS

Complementary design

<>

Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

SPECIFICATIONS

Accessories

| | |
|------------|---|
| Wire shelf | 1 |
|------------|---|

Capacity

| | |
|--------------------------|------|
| Accessory rack maximum | 42lb |
| Cappuccino cups | 24 |
| Espresso cups | 54 |
| Maximum allowable weight | 55lb |
| Place settings | 16 |
| Usable depth | 16 |
| Usable height | 9 |
| Usable width | 21 |

Cleaning

| | |
|------------------------------|---|
| Easy clean smooth-glass base | • |
|------------------------------|---|

Controls

| | |
|----------------------------|--------------------------|
| Audio feedback | • |
| Automatic timers | 30', 45', 1h, 2h, 4h, 6h |
| Delayed start | • |
| Interior light | LED |
| Intuitive capacitive touch | • |
| On/Off indicator | • |
| Pre-set heating functions | • |
| Sabbath mode | • |
| Soft close drawer | • |
| Standby mode | • |

Functions

| | |
|---------------------|---|
| Cups | • |
| Dehydrate | • |
| Number of functions | 6 |
| Plates | • |
| Rapid proof | • |
| Slow cook | • |
| Warm | • |

Performance

| | |
|---------------------------|------------|
| Heated glass base and fan | • |
| Low temperature cooking | • |
| Temperature levels | 6 |
| Temperature range | 95°F-185°F |

Power requirements

| | |
|----------|-----|
| Amperage | 10A |
|----------|-----|

| | |
|-------------------|-------------------------------|
| Maximum power | 810W |
| Power cord length | 70 |
| Power outlet | 3-prong grounding-type |
| Supply frequency | 60Hz |
| Supply voltage | 110V |

Product dimensions

| | |
|--------------------------------|------------------------------------|
| Adjustable front door panel to | • |
| Depth | 22 ³ / ₈ " |
| Height | 10 ¹¹ / ₁₆ " |
| Width | 29 ¹⁵ / ₁₆ " |

Safety

| | |
|-----------------------------|---|
| Automatic turn off after 12 | • |
| Full extension telescopic | • |

Warranty

| | |
|-----------------|----------------|
| Parts and labor | 2 years |
|-----------------|----------------|

| | |
|-----|-------|
| SKU | 82115 |
|-----|-------|

Other product downloads available at fisherpaykel.com

- [↓](#) User Guide
- [↓](#) Service & Warranty Booklet
- [↓](#) Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020