

---

## CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

---

## GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

---

## ASSEMBLY AND INSTALLATION

1. Pull the SUPPLY WIRES (5 & 6) and the HOUSE GROUND WIRE (7) out from the OUTLET BOX (1)(no include) and attach the MOUNTING BRACKET (2) to the OUTLET BOX (1)(no include) using the slotted holes on the MOUNTING BRACKET (2) and the MOUNTING SCREWS (3) provided.
2. Thread the FIXTURE SCREWS (4) two full turns into the appropriate threaded holes in the MOUNTING BRACKET (2). (Check the MOUNTING BRACKET (2) against the fixture KEY HOLE SLOTS (13) to ensure proper fit.)
3. Attach the power supply wires to the fixture lead wires by connecting the BLACK FIXTURE WIRE (9) to the BLACK SUPPLY WIRE (6), and the WHITE FIXTURE WIRE (10) to the WHITE SUPPLY WIRE (5) using WIRE CONNECTOR (8). Connect the remaining FIXTURE GROUND WIRE (14) to the SUPPLY GROUND WIRE (7) using a WIRE CONNECTOR (8). Place wiring and connections inside the OUTLET BOX (1)(no include)
4. Carefully tuck all wiring back into the OUTLET BOX (1)(no include). Locate the FIXTURE PAN (12) over the OUTLET BOX (1)(no include), positioning the FIXTURE SCREW (4) heads through the large openings of the KEY HOLE SLOTS (13). Rotate the FIXTURE PAN (12) to seat the screws, and tighten securely. (see Fig. 2)

## ASSEMBLY AND INSTALLATION (Continued)

5. Install the bulbs. (See markings and/or labels on the fixture for maximum wattages - DO NOT OVER-LAMP.)
6. Screw the THREADED PIPE (17) onto center COUPLING (18) of the FIXTURE PAN (12). Install the GLASS SHADE (11) and CAP (15) onto the THREADED PIPE (17) and secure using the FINIAL KNOB (16). (See Fig. 1)

## INSTALLATION IS NOW COMPLETED

