4

CODE ID

30" PROFESSIONAL HOOD

F6PH30S1

1 FAN - SLIDER





Filtering



CFM max 600



2 LED lamps



Noise Level 72 (dB)



Wall hung installation

CODE ID

F6PH30S2

1 FAN - KNOBS



Filtering



CFM max 600



4 LED lamps



Noise Level 72 (dB)



Wall hung installation



## HOOD F6PH30S2

Scotch brite stainless steel (AISI 430) Heavy Duty Control Panel with Knobs 4 Speed - Mechanical Control LED lighting: Led 4x1.2 W - 3200 K One fan motor CFM max 600 72 dB sound rating Baffle filter

### Minimum distance:

- Electric hob 20 1/2" - 52 cm - Gas hob 24 3/4" - 63 cm

## HOOD F6PH30S1

Scotch brite stainless steel (AISI 430) Slider controls LED lighting: Led 2x1.2 W - 3200 K One fan motor CFM max 600 72 dB sound rating Baffle filter

# Minimum distance:

- Electric hob 20 1/2" - 52 cm - Gas hob 24 3/4" - 63 cm


## **OPTIONAL ACCESSORIES**

F6CK30-12 FMFIL Chimney cover Charcoal filter

www.fulgor-milano.com FULGOR MILANO

30" PROFESSIONAL HOOD





CODE ID	F6PH30S1 - F6PH30S2 - 30" PROFESSIONAL HOOD	
Series and Finish	600 Series - Professional Design - Stainless Steel (AISI 430)	
CONTROL PANEL		
Control Type	4 speed mechanical control	
PERFORMANCES		
Output (CFM)	600	
Sound Level (dB)	72	
Motor	One	
Venting Type	Ducted and recirculating	
FEATURES		
Filter Style	2 x 1.2W LED	
Lighting	4 x 1.2W LED	,
Single duct diameter	5 - 15/16"	(200 mm)
DIMENSIONS/WEIGHT		
Overall dim - Width	29 - 13/16"	(760 mm)
Overall dim - Height	18"	(460 mm)
Overall dim - Depth	24"	(610 mm)
Gross Weight	61 lbs	(28 kg)
POWER / RATINGS (115 V, 60 HZ)		
Watts / Amps	430W - 3.8A	
Power Cable	Nema 5-15P	
INSTRUCTIONS FOR USE		
Use & Care Manual / Installation Manual	English / French / Spanish	

www.fulgor-milano.com FULGOR MILANO