

GENERAC®

EXCLUSIVE GENERAC BLENDED ENGINE OIL

FULL SYNTHETIC 5W-20 GEO

DESCRIPTION

Generac's Proprietary Blend is a full synthetic SAE 5W-20 low ash gaseous (natural gas and propane) engine oil. It contains newly developed antioxidants/detergents to protect against fluid degradation and provides extremely long oil life. It contains ZDDP and other anti-wear additives for component protection. This synthetic base oil allows for great starting at low temperature and low volatility at high temperatures.

BENEFITS

- **Specifically designed** for Generac natural gas and propane standby generators
- **Optimized** for high-demand equipment
- **Low viscosity drag** — Higher horsepower, better fuel economy and overall engine performance
- **Low ash formula** — Improved valve performance and maximum engine protection
- **Improved Detergency** — Cleaner pistons and engines for increased wear protection
- **Improved corrosion protection** — Protection against crankcase moisture
- **Low volatility** — Less oil consumption, less top-offs, more time in your schedule
- **Available** in 1qt. (0.95L) bottle, 5qt. (4.7L) jug, and 55gal (208L) drum

APPLICATION

Developed specifically for Generac natural gas and propane standby generator applications.

Highly recommended for use on equipment furnished with cold weather kits and starting aids.



TYPICAL PROPERTIES

5W-20

Viscosity, cSt @ 104°F / 40°C	ASTM D445	47.1
Viscosity, cSt @ 212°F / 100°C	ASTM D445	8.2
Viscosity Index	ASTM D2270	148
Cold Crank, -30°C (86°F), cP	ASTM D5293	5,874
Flash Point	ASTM D92	464°F / 240°C
Pour Point	ASTM D97	32.8°F / -36°C
API, 15.6°C (60.08°F)	ASTM D1298	35.0
Specific Gravity, 15.6°C (60.08°F)	ASTM 1298	0.850
Density, 15.6°C (60.08°F), lbs/Gallon	ASTM 1298	7.08
Volatility (NOACK)	ASTM D5800	6.5
HTHS, 150°C (302°F), cP	ASTM 4683	2.7
MRV, -35°C (-31°F), cP	ASTM 4684	16,604
Base Number (TBN), mg/KOH/g	ASTM 2896	7.3
Sulfated Ash, % mass	ASTM D874	0.5
Zinc, % mass	ASTM D5185	0.033
Phosphorus, % mass	ASTM D5185	0.030
Calcium, % mass	ASTM 5185	0.132

DISTRIBUTOR/DEALER ENGINE OIL PROGRAM

- All orders must be placed through Generac. See details below on how to order.
- One (1) pallet minimum if ordering from vendor Lube-Tech
- One (1) case minimum if ordering from Generac JDC
- Features 5W-20 GEO Full Synthetic, 5W-30 Full Synthetic, and 15W-40 (see below for bottle size availability)
- Products will ship from either Generac or direct from LubeTech - see chart below for details by part number
- All part numbers listed below count toward total Generac part purchases

PART #	GENERAC BRANDED OIL - SHIPS FROM VENDOR LUBE-TECH 1 PLT MINIMUM	QTY PER PALLET
A0001412868	5W-20 GEO Full Synthetic – 1 quart / 0.95L bottle, case of 12	70
A0001412873	5W-20 GEO Full Synthetic – 55 gallon / 208L drum	4
OJ5324A	5W-30 Full Synthetic – 1 quart / 0.95L jug, case of 12	70
OJ5323A	5W-30 Full Synthetic – 5 quart / 4.7L jug, 3-pack	54
OJ5322A	5W-30 Full Synthetic – 55 gallon / 208L drum	4
OJ5160A	15W-40 CK-4 Heavy Duty Synthetic Blend – 1 gallon / 3.8L jugs, 3-pack	54
OJ5171	15W-40 CK-4 Heavy Duty Synthetic Blend – 5 gallon / 19L pail	36
OJ5159A	15W-40 CK-4 Heavy Duty Synthetic Blend – 55 gallon / 208L drum	4

PART #	GENERAC BRANDED OIL - SHIPS FROM GENERAC DIST. CENTER 1 CASE MINIMUM	QTY PER CASE
A0001412864	5W-20 GEO Full Synthetic – 1 quart / 0.95L bottle	12
A0001412871	5W-20 GEO Full Synthetic – 5 quart / 4.7L jug	3
OJ5141	5W-30 Full Synthetic – 1 quart / 0.95L bottle	12
OJ5146	15W-40 CK-4 Heavy Duty Synthetic Blend – 1 gallon / 3.8L jug	3



PLACE YOUR OIL ORDER TODAY

Accounts with access to GENservice, place all orders through the portal.

Accounts without access to GENservice, contact AfterSales@generac.com for price inquiries and placing orders.