# **FUNCTIONS**

## Passage Set

Active latch with no locking mechanism. Knob is always unlocked. **SPECIFY HANDING** on all split finishes and all rosettes with levers. Standard door range: 1-3/8" to 1-3/4" thick, extendable to 2-1/2" with kit.



#### Dummy

Non-functioning door set with no latch and no locking mechanism, used on one side of door (typically used with roller catch, flush bolts or surface bolts). Surface mounted. **SPECIFY HANDING** on all designs with levers.



# **Double Cylinder Deadbolt**

Manually operated bolt for entry door with keyed cylinder on both the exterior and interior. Standard door range: 1-3/4" to 2-1/4" thick, extendable to 2-1/2" with kit.



#### Combo Pack

Matching passage set and single cylinder deadbolt. **SPECIFY HANDING** on all split finishes and all rosettes with levers. Standard door range: 1-3/4" to 2-1/4" thick, extendable to 2-1/2" with kit.





## **Privacy Lock**



Active latch with locking mechanism. Privacy pin provides locking through rose or long plate. **SPECIFY HANDING** on all split finishes and all rosettes with levers. Standard door range: 1-3/8" to 1-3/4" thick, extendable to 2-1/2" with kit.



## **Double Dummy**

Two non-functioning door sets (with no latch) are used on both sides of a door, or on side-by-side or French doors (typically used with roller catch, flush bolts or surface bolts). Surface mounted or thru-bolted. **SPECIFY HANDING** on all split finishes.



# Single Cylinder Deadbolt

Manually operated bolt for entry door with keyed cylinder on the exterior and thumbturn on the interior. Standard door range: 1-3/4" to 2-1/4" thick, extendable to 2-1/2" with kit.



# Complete Handleset (Single Cylinder)

Thumb-operated latch with keyed deadbolt paired with an active latch set with thumbturnoperated deadbolt. Standard door range: 1-3/4" to 2-1/4" thick, extendable to 2-1/2" with kit.