





Submittal Data: TERRA12HP230V1A			12,000 BTU/H Wall Mounted Heat- Pump System																												
Job Name		Location		Date																											
Purchaser		Engineer																													
Submitted To		For		<input type="checkbox"/> Reference	<input type="checkbox"/> Approval	<input type="checkbox"/> Construction																									
Unit Designation		Schedule No.																													
GENERAL FEATURES <ul style="list-style-type: none">- Ultra High Efficiency- 7 Indoor Fan Speeds- 4 Way Airflow Operation-Photocatalytic Filter-Wireless Remote with LCD Display-Gold Fin Condenser Coil-5 year Limited Parts Warranty-7 year Limited Compressor Warranty			    <div>AHRI Certified Ref No: 7077794</div>																												
System Ratings			Indoor Unit Data																												
Cooling <table><tr><td>Rated Capacity</td><td>12000 BTU/H</td></tr><tr><td>Capacity Range</td><td>3,100-13,000 BTU/H</td></tr><tr><td>Power Input (Max)</td><td>1,300 W</td></tr><tr><td>SEER</td><td>25</td></tr><tr><td>EER</td><td>12.8</td></tr></table>			Rated Capacity	12000 BTU/H	Capacity Range	3,100-13,000 BTU/H	Power Input (Max)	1,300 W	SEER	25	EER	12.8	Fan Motor <table><tr><td>Output Power</td><td>10 W</td></tr><tr><td>FLA</td><td>0.1 A</td></tr></table> Airflow <table><tr><td>Cooling Wet (Lo/Hi)</td><td>112/430 CFM</td></tr><tr><td>Heating Dry (Lo/Hi)</td><td>118/453 CFM</td></tr></table> Sound Pressure Level <table><tr><td>Cooling (Lo/Hi)</td><td>34/44 db(A)</td></tr><tr><td>Heating (Lo/Hi)</td><td>34/44 db(A)</td></tr></table> Dimensions & Weights <table><tr><td>Unit Dimensions (LxHxD)</td><td>34.1 x 11.5 x 8.2-in</td></tr><tr><td>Weight (Net/Shipping)</td><td>24/31 LBS</td></tr></table>			Output Power	10 W	FLA	0.1 A	Cooling Wet (Lo/Hi)	112/430 CFM	Heating Dry (Lo/Hi)	118/453 CFM	Cooling (Lo/Hi)	34/44 db(A)	Heating (Lo/Hi)	34/44 db(A)	Unit Dimensions (LxHxD)	34.1 x 11.5 x 8.2-in	Weight (Net/Shipping)	24/31 LBS
Rated Capacity	12000 BTU/H																														
Capacity Range	3,100-13,000 BTU/H																														
Power Input (Max)	1,300 W																														
SEER	25																														
EER	12.8																														
Output Power	10 W																														
FLA	0.1 A																														
Cooling Wet (Lo/Hi)	112/430 CFM																														
Heating Dry (Lo/Hi)	118/453 CFM																														
Cooling (Lo/Hi)	34/44 db(A)																														
Heating (Lo/Hi)	34/44 db(A)																														
Unit Dimensions (LxHxD)	34.1 x 11.5 x 8.2-in																														
Weight (Net/Shipping)	24/31 LBS																														
Heating at 47° F <table><tr><td>Rated Capacity</td><td>13,000 BTU/H</td></tr><tr><td>Capacity Range</td><td>2,400-14,000 BTU/H</td></tr><tr><td>Power Input (Max)</td><td>1,350 W</td></tr><tr><td>HSPF</td><td>9.0</td></tr><tr><td>COP</td><td>3.5</td></tr></table>			Rated Capacity	13,000 BTU/H	Capacity Range	2,400-14,000 BTU/H	Power Input (Max)	1,350 W	HSPF	9.0	COP	3.5	Outdoor Unit Data Compressor DC Inverter Driven Rotary Refrigerant Type R410A Fan Motor <table><tr><td>Output Power</td><td>40 W</td></tr><tr><td>FLA</td><td>0.2 A</td></tr></table> Sound Pressure <table><tr><td>Cooling (Lo/Hi)</td><td>49/59 db(A)</td></tr><tr><td>Heating (Lo/Hi)</td><td>49/59 db(A)</td></tr></table> Dimensions & Weights <table><tr><td>Unit Dimensions (LxHxD)</td><td>35.4 x 23.5 x 14.9 -in</td></tr><tr><td>Weight (Net/Shipping)</td><td>87/92 LBS</td></tr></table>			Output Power	40 W	FLA	0.2 A	Cooling (Lo/Hi)	49/59 db(A)	Heating (Lo/Hi)	49/59 db(A)	Unit Dimensions (LxHxD)	35.4 x 23.5 x 14.9 -in	Weight (Net/Shipping)	87/92 LBS				
Rated Capacity	13,000 BTU/H																														
Capacity Range	2,400-14,000 BTU/H																														
Power Input (Max)	1,350 W																														
HSPF	9.0																														
COP	3.5																														
Output Power	40 W																														
FLA	0.2 A																														
Cooling (Lo/Hi)	49/59 db(A)																														
Heating (Lo/Hi)	49/59 db(A)																														
Unit Dimensions (LxHxD)	35.4 x 23.5 x 14.9 -in																														
Weight (Net/Shipping)	87/92 LBS																														
Heating at 17° F <table><tr><td>Rated Capacity</td><td>11,231 BTU/H</td></tr><tr><td>Capacity (Max)</td><td>12,095 BTU/H</td></tr><tr><td>Power Input (Max)</td><td>1,166 W</td></tr><tr><td>COP</td><td>2.6</td></tr></table>			Rated Capacity	11,231 BTU/H	Capacity (Max)	12,095 BTU/H	Power Input (Max)	1,166 W	COP	2.6	Refrigerant Piping Data <table><tr><td>Gas Pipe Size (OD)</td><td>1/2-in</td></tr><tr><td>Liquid Pipe Size (OD)</td><td>1/4-in</td></tr><tr><td>Connection Method</td><td>Flared</td></tr><tr><td>MAX Refrigerant Pipe Length</td><td>66-ft</td></tr><tr><td>MIN Refrigerant Pipe Length</td><td>10-ft</td></tr><tr><td>MAX Refrigerant Pipe Height Difference</td><td>33-ft</td></tr></table>			Gas Pipe Size (OD)	1/2-in	Liquid Pipe Size (OD)	1/4-in	Connection Method	Flared	MAX Refrigerant Pipe Length	66-ft	MIN Refrigerant Pipe Length	10-ft	MAX Refrigerant Pipe Height Difference	33-ft						
Rated Capacity	11,231 BTU/H																														
Capacity (Max)	12,095 BTU/H																														
Power Input (Max)	1,166 W																														
COP	2.6																														
Gas Pipe Size (OD)	1/2-in																														
Liquid Pipe Size (OD)	1/4-in																														
Connection Method	Flared																														
MAX Refrigerant Pipe Length	66-ft																														
MIN Refrigerant Pipe Length	10-ft																														
MAX Refrigerant Pipe Height Difference	33-ft																														
Operating Range <table><tr><td>Cooling</td><td>(Max)</td><td>118°F (48 C)</td></tr><tr><td></td><td>(Min)</td><td>5°F (-15 C)</td></tr><tr><td>Heating</td><td>(Max)</td><td>75°F (24 C)</td></tr><tr><td></td><td>(Min)</td><td>5°F (-15 C)</td></tr></table>			Cooling	(Max)	118°F (48 C)		(Min)	5°F (-15 C)	Heating	(Max)	75°F (24 C)		(Min)	5°F (-15 C)																	
Cooling	(Max)	118°F (48 C)																													
	(Min)	5°F (-15 C)																													
Heating	(Max)	75°F (24 C)																													
	(Min)	5°F (-15 C)																													
Power Supply <table><tr><td>Normal Operational Voltage</td><td>208/230 V, 1 Phase, 60 Hz</td></tr><tr><td>Voltage Range</td><td>187 - 253V</td></tr><tr><td>Main Power Wire Size</td><td>14-2 AWG</td></tr><tr><td>Interconnecting Cable Wire Size</td><td>14-4 AWG</td></tr><tr><td>MCA</td><td>10 A</td></tr><tr><td>MOCP/Breaker Size</td><td>15 A</td></tr></table>			Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz	Voltage Range	187 - 253V	Main Power Wire Size	14-2 AWG	Interconnecting Cable Wire Size	14-4 AWG	MCA	10 A	MOCP/Breaker Size	15 A																	
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz																														
Voltage Range	187 - 253V																														
Main Power Wire Size	14-2 AWG																														
Interconnecting Cable Wire Size	14-4 AWG																														
MCA	10 A																														
MOCP/Breaker Size	15 A																														
