

26 123

RETRO-FIT™

210 SHOWER SYSTEM

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE DreamSpray®
- GROHE EcoJoy®
- Speed Clean® anti-lime system
- Wall mounted diverter shower system
- 17 1/16" Optional fixed or swivel Rainshower™ shower arm
- Switch between hand shower and shower head or dual function via built-in diverter
- 6 diverter functions (2 discrete functions (non shared) + one shared function in both standard and Eco flow)
- Adjustable height bar with gliding element
- Distance between diverter and upper bracket 25 3/4" (653 mm)
- Angle adapter to prevent hose interfering with shower valve
- System includes 2 back flow preventers
- 59" Metal shower hose (28 417)
- Tempesta® 210 shower head, 1.75gpm (26 409)
- 1 Spray: Rain
- Tempesta® 100 hand shower, 1.75gpm (26 047)
- 2 Adjustable spray patterns: Rain, Jet
- GROHE Retro-Fit™ shower system (26 485)
- Optional: Wall spacer for upper bracket (26 030) (sold separately)
- Optional: Shower system 6" height extension (26 464) (sold separately)



PRODUCT FEATURES:

- GROHE StarLight®
- GROHE CoolTouch®
- GROHE DreamSpray®
- Speed Clean®

CERTIFICATIONS:



- WaterSense
- CEC Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

- 26123001** GROHE StarLight® Chrome
- 261232431** Matte Black
- 26123EN1** Brushed Nickel InfinityFinish™
- 26123GN1** Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-04-2023

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

26 123

RETRO-FIT™

210 SHOWER SYSTEM

Pure Freude
an Wasser



TECHNICAL DATA:

Product Height	32-9/16 in
Product Length	21-7/8 in
Product Width	8-1/4 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min

