
### RAINSHOWER 310 SMARTACTIVE Shower Head Set 2 Sprays MODEL # 26502EN0
















Product Description: RAINSHOWER 310 SMARTACTIVE Shower Head Set 2 Sprays

#### Standard Specification:

- Consisting of:
- Rainshower 310 SmartActive shower head Brushed Nickel
- 2 Spray patterns:
- GROHE PureRain, ActiveRain
- Includes 16" shower arm

**GROHE EcoJoy** 1.75 gpm flow limiter per each water way

- GROHE DreamSpray perfect spray pattern
- GROHE StarLight finish
- SpeedClean® anti-lime system
- Inner WaterGuide for a longer life
- Rough-in set for shower head
- 2-Way diverter rough-in set 29 900 000 (Trim set to be ordered separately)

#### Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations

Color: 26502EN0 Brushed Nickel

### CONCETTO 2-Way Diverter Trim (Shower head/Hand Shower) MODEL # 29108001







# 4<sup>13</sup>/<sub>16</sub>" (122) 2<sup>5</sup>/<sub>8</sub>"

## ADA

Product Description: CONCETTO 2-Way Diverter Trim (Shower head/Hand Shower)

### Standard Specification:

- GROHE StarLight chrome finish
- Metal lever handle for 2 outlets: shower head/hand shower
  For use with 2-way diverter rough-in valves (29 900) or (29
- 901)
- ADA Compliant

### Applicable Codes & Standards:

• ICC/ANSI A117.1

Color: 29108001 StarLight Chrome


# GROHTHERM SMARTCONTROL Single Function Thermostatic Trim with Control Module

Pure Freude an Wasser

MODEL # 29136EN0

GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com





 $\frac{11}{16''}$ 



#### Standard Specification:

- Final installation set for:
- Required rough-in-set sold separately (GROHE Rapido SmartBox 35 601 000)
- Metal wall escutcheon with **GROHE QuickFix** (covered escutcheon and shaft sealing, covered fixing), 6° angle adjustable
- 3/8" (10mm) thin profile escutcheon
- GROHE StarLight finish
- SmartControl push for ON-OFF, turn for volume adjustment from EcoJoy to Full Flow
- Includes various icons to customize push buttons
- **GROHE TurboStat** Compact cartridge with wax thermoelement
- GROHE SafeStop safety button at 100°F/38°C
- Built-in check valve with dirt strainer
- Maximum flow performance: 7.7gpm (29L/min) @ 43.5 psi (3 bar)
- Optional flow reducer for CALGreen compliance included

### Applicable Codes & Standards:

- ASME A112.18.1/CSA B125.1
- CalGreen

Color: 29136EN0 Brushed Nickel

### RAPIDO SMARTBOX Universal Rough-In Box MODEL # 35601000

# Pure Freude an Wasser



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com





### Standard Specification:

- 3 outlets 1/2" Female NPT
- 2 intlets 1/2" Female NPT
- Installation depth 3"-4" (75-105 mm)
- Pre-mounted flushing plug
- Stable built-in box and plaster guard
- Mounting options for solid walls and dry walls
- Trim not included

### Applicable Codes & Standards:

• ASME A112.18.1/CSA B125.1

Color: a 35601000 StarLight Chrome

