32 665

CONCETTO™

Pure Frende an Wasser

SINGLE-HANDLE PULL-DOWN KITCHEN FAUCET DUAL SPRAY 1.75 GPM

STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- Speed Clean® anti-lime system
- GROHE StarLight® Finish
- 15" Faucet height
- 7 3/8" Aerator height
- 8 3/4" Faucet reach
- 360° Swivel radius
- Dual spray with toggle function: switches between regular water flow and spray without turning off the water
- GROHE QuickFix® Plus installation system
- 1.75gpm
- CALGreen compliant
- Compatible with GROHE Foot Control retro-fit set (30 310 000)
- Optional quick coupling to reduce flow: (64 999 000) - 1.5gpm, (40 985 000) - 1.0gpm



PRODUCT FEATURES:



GROHE StarLight®



GROHE SilkMove®



Speed Clean®

CERTIFICATIONS:



- CEC Certified
- Low Lead Certified
- **CALGreen Compliant**
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- ASMF A112.18.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:

32665003

GROHE StarLight® Chrome

326652433



32665DC3

SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 06-03-2022

US

Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.

Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



32 665

CONCETTOTM



SINGLE-HANDLE PULL-DOWN KITCHEN FAUCET DUAL SPRAY 1.75 GPM

TECHNICAL DATA:

Product Height 15 in

Product Length 9-3/4 in

Product Width 5-3/8 in

Fitting Spout Height 7-3/8 in

Fitting Spout Reach 8-3/4 in

GPM (Min)-GPM (Max) 1.75 gal (US)/min

Fitting No of Holes Required 1

