




Position	Count	Description	Unit price
	-1	<p><b>TP 50-240/2 U-G-A-BUBE</b></p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 96411818 Single-stage centrifugal in-line single-head pump.</p> <p>The in-line design with opposite suction and discharge ports enables mounting in pipework or on a concrete foundation.</p> <p>The shaft seal is a corrosion-resistant maintenance-free mechanical seal.</p> <p>The motor is a 1-phase AC motor.</p> <p><b>Liquid:</b>            Liquid temperature range: 5 .. 284 °F            Density: 62.4 lb/ft³</p> <p><b>Technical:</b>            Speed for pump data: 3490 rpm            Rated flow: 101 US gpm            Rated head: 48.6 ft            Shaft seal: BUBE            Maximum operating pressure: 145 psi            Approvals on motor nameplate: UL Recognized Component, CSA</p> <p><b>Materials:</b>            Pump housing: Cast iron                              EN-JL1040                              ASTM 25 B            Impeller: Stainless steel                              DIN W.-Nr. 1.4301                              AISI 304</p> <p><b>Installation:</b>            Maximum ambient temperature: 104 °F            Maximum operating pressure: 145 psi            Flange standard: USA            Pipe connection: 2"</p> <p><b>Electrical data:</b></p>	On request



Company name: -  
 Created by: -  
 Phone: -  
 Fax: -  
 Date: -

Position	Count	Description	Unit price
		Motor type: Baldor, TEFC Number of poles: 2 Rated power - P2: 2.01 HP Main frequency: 60 Hz Rated voltage: 1 x 115/230 V Service factor: 1,15 Rated current: 23/11,5 A Starting current: 156/78 A Cos phi - power factor: 82 Rated speed: 3450 rpm Motor efficiency at full load: 74 % Insulation class (IEC 85): F  Others: Net weight: 88.4 lb Gross weight: 96.1 lb Shipping volume: 2.33 ft <sup>3</sup>	

Description	Value
Product name:	TP 50-240/2 U-G-A-BUBE U-G-A-BUBE
Product Number:	96411818
EAN number:	5700390524920
<b>Technical:</b>	
Speed for pump data	3490 rpm
Rated flow:	101 US gpm
Rated head:	48.6 ft
Head max:	78.7 ft
Shaft seal:	BUBE
Maximum operating pressure	145 psi
Approvals on motor nameplate:	UL Recognized Component, CSA
Pump Number:	96405267
Pump version:	U
<b>Materials:</b>	
Pump housing:	Cast iron EN-JL1040 ASTM 25 B
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Material code:	A
<b>Installation:</b>	
Maximum ambient temperature:	104 °F
Maximum operating pressure	145 psi
Flange standard:	USA
Connect code:	G
Pipe connection:	2"
<b>Liquid:</b>	
Liquid temperature range	5 .. 284 °F
Density:	62.4 lb/ft <sup>3</sup>
<b>Electrical data:</b>	
Motor type:	Baldor, TEFC
Number of poles:	2
Rated power - P2:	2.01 HP
KVA code:	K
Main frequency:	60 Hz
Rated voltage:	1 x 115/230 V
Service factor:	1,15
Rated current:	23/11,5 A
Starting current	156/78 A
Load current:	25,8/12,9 A
Cos phi - power factor:	82
Rated speed:	3450 rpm
Motor efficiency at full load:	74 %
Insulation class (IEC 85):	F
Motor protection:	CONTACT
Thermal protec:	internal
Motor Number:	85700006
<b>Others:</b>	
Net weight:	88.4 lb
Gross weight:	96.1 lb
Shipping volume:	2.33 ft <sup>3</sup>
Country code:	Namreg

