

Miniwinch

- For wood doors, with adjustable opening angle and braking effect and soft open and soft closing mechanism
- No time-consuming cabinet processing requiredFor horizontal or vertical installation (extremely little space
- required inside the cabinet)
- Suitable for left or right hand use
- Internal cabinet depth: min. 196 mm (7 11/16") (horizontally), min. 110 mm (4 5/16") (vertically)
- For door height: 200 480 mm (7 7/8" 18 7/8")
- Max. door weight: 12 kg (26 lbs.)
- For screw mounting with Euro screws
- W x L x D: 89 x 23 x 163 mm (3 1/2" x 15/16" x 6 7/16") when installed horizontally

Adjustment



Opening angle adjustment Opening speed adjustment

Note Lower door weight during adjustment.

Vertical installation



Fitting

Material: Fitting; Plastic; Color: gray Front Fixing Brackets: Zinc Alloy Finish: nickel-plated; Cover Caps: Plastic


Model	Silver Colored Matt Cover Caps	Black Cover Caps
А	365.47.931	365.47.331
В	365.47.932	365.47.332
С	365.47.933	365.47.333
D	365.47.934	365.47.334
E	365.47.935	365.47.335
F	365.47.936	365.47.336

Supplied With

Front fixing bracket Cover cap Mounting material

Planning and installation


Horizontal installation




U	V	W	Х
200–330	194	102	137 + Z
330–430	218	126	161 + Z
430–480	228	136	171 + Z

$ \begin{array}{c} 05 \times 12 \\ (3/16" \times 1/2") \\ \hline 185 \\ (75/16") \\ \hline 66 \\ (33/8") \\ \hline 54 \\ \hline (11/2") \\ (11/2") \\ (11/2") \\ \hline 110 \\ \hline \end{array} $	U U 11/16")
⊲ 110 ► (4 5/16")	

U	Х
200–400	161 + Z



Y = lateral door overlay dimension Z = bottom door overlay dimension



9

Dimensions in mm Inches are approximate

