



## HAWA Junior 80/GS

### Set

- For 1 sliding door without upper track and lower guide channel

|  | Item No.   |
|--|------------|
|  | 940.81.000 |

### Supplied With

Mounting instructions




### Set Components

|                                                                                     | Description                                         | Material | Finish | Qty.   | Item No.   |
|-------------------------------------------------------------------------------------|-----------------------------------------------------|----------|--------|--------|------------|
|    | Double roller running gear                          | –        | –      | 2 pcs. | 940.80.012 |
|    | Suspension bolt, M10                                | –        | –      | 2 pcs. | 941.00.072 |
|    | Clamp shoe, adjustable from 6 – 12.7 (1/4" – 1/2")  | Aluminum | –      | 2 pcs. | 941.00.020 |
|    | Track stopper with adjustable retention spring      | –        | –      | 2 pcs. | 940.80.040 |
|   | Floor guide, adjustable from 6 – 12.7 (1/4" – 1/2") | –        | –      | 1 pc.  | 941.00.031 |
|  | Buffer                                              | Rubber   | black  | 1 pc.  | 407.01.930 |

### Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.

### Individual Components

|                                                                                     | Description                                            | Material | Finish         | Length             | Item No.   |
|-------------------------------------------------------------------------------------|--------------------------------------------------------|----------|----------------|--------------------|------------|
|  | Upper track, pre-drilled                               | Aluminum | clear anodized | 1.4 m (4' 7 1/8")  | 940.80.140 |
|                                                                                     |                                                        |          |                | 1.6 m (5' 3")      | 940.80.160 |
|                                                                                     |                                                        |          |                | 1.8 m (5' 10 7/8") | 940.80.180 |
|                                                                                     |                                                        |          |                | 2 m (6' 6 3/4")    | 940.80.200 |
|                                                                                     |                                                        |          |                | 2.2 m (7' 2 5/8")  | 940.80.220 |
|                                                                                     |                                                        |          |                | 2.5 m (8' 2 7/16") | 940.80.250 |
|                                                                                     |                                                        |          |                | 3 m (9' 10 1/8")   | 940.80.300 |
|                                                                                     |                                                        |          |                | 4 m (13' 1 1/2")   | 940.80.400 |
|                                                                                     |                                                        |          |                | 6 m (19' 8 1/4")   | 940.80.600 |
|  | Gliders, self adhesive, for 8 mm (5/16") thick glass   | Plastic  | –              | –                  | 940.40.033 |
|  | Gliders, self adhesive, for 10 mm (13/32") thick glass | Plastic  | –              | –                  | 940.40.034 |
|  | Lower guide channel, 20 x 20 mm (25/32" x 25/32")      | Aluminum | anodized       | 2.5 m (8' 2 7/16") | 941.00.925 |
|                                                                                     | Lower guide channel, 20 x 20 mm (25/32" x 25/32")      |          |                | 6 m (19' 8 1/4")   | 941.00.960 |

|                                            |                   |
|--------------------------------------------|-------------------|
| Angle profile                              | page 1.288        |
| Toplock                                    | pages 1.352-1.356 |
| Clip-on fascias and end caps to clamp shoe | page 1.219        |
| Floor mounted door stop                    | page 1.290        |
| Glass edge protection profiles             | page 1.291        |
| Soft close                                 | page 1.287        |

Dimensions in mm  
Inches are approximate