Surface mounted light bars

With inline dimmer switch, 12 V, linkable

Profile 2103 with Loox LED 2068



Inline dimmer switch is concealed below the diffuser.

> CRI 90 lights are Title 24 compliant
> Life time: 30,000 hours
> Supplied ready to install
> Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
> Linkable to other light bars see page 73

5 12 V Loox5 12 V driver see page 130

Note
Loox lights and drivers are "Suitable for use within closet storage spaces"

3000 K	4000 K	120°		
2250 lx	2300 lx		250 mm	(9 13/16")
940 lx	950 lx		500 mm	(19 11/16")
505 lx	510 lx		750 mm	(29 1/2")
310 lx	320 lx		1000 mm	(39 3/8")

Components

> Profile:	2103 - see page 34.
> LED strip:	2068 - see page 10.
> Mounting brackets:	see page 36.
> Inline touch dimmer:	833.89.281 - see page 87.

Light Color (K)	**3000 (warm white)**				**4000 (cool white)**			
Lumen per watt	**101**				**104**			
Item No.	**833.70.647**	**833.70.648**	**833.70.649**	**833.70.650**	**833.70.661**	**833.70.662**	**833.70.663**	**833.70.664**
Length	152 (6")	229 (9")	305 (12")	381 (15")	152 (6")	229 (9")	305 (12")	381 (15")
Wattage	0.7	1.4	2.2	2.9	0.7	1.4	2.2	2.9
LEDs	9	18	27	36	9	18	27	36
Lumen	73	146	218	291	75	150	225	300
Item No.	**833.70.651**	**833.70.652**	**833.70.653**	**833.70.654**	**833.70.665**	**833.70.666**	**833.70.667**	**833.70.668**
Length	457 (18")	533 (21")	610 (24")	686 (27")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	3.6	4.3	5	5.8	3.6	4.3	5	5.8
LEDs	45	54	63	72	45	54	63	72
Lumen	364	437	509	582	375	450	525	600
Item No.	**833.70.655**	**833.70.656**	**833.70.657**	**833.70.658**	**833.70.669**	**833.70.670**	**833.70.671**	**833.70.672**
Length	762 (30")	832 (33")	915 (36")	991 (39")	762 (30")	832 (33")	915 (36")	991 (39")
Wattage	6.5	7.2	7.9	8.6	6.5	7.2	7.9	8.6
LEDs	81	90	99	108	81	90	99	108
Lumen	655	728	800	873	675	750	825	900
Item No.	**833.70.659**		**833.70.660**		**833.70.673**		**833.70.674**	
Length	1067 (42")		1143 (45")		1067 (42")		1143 (45")	
Wattage	9.4		10.1		9.4		10.1	
LEDs	117		126		117		126	
Lumen	946		1019		975		1050	
CRI	90*							
Material	Aluminum; Lens: Plastic, opal							
Supplied with	2000 mm (78 3/4") driver connection cable with integrated switch, 100 mm (4") female mini driver cable, mounting brackets							

*JA8-2016-E R36733 IP20

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.