


Surface mounted light bars

With linkable cable, 12 V

Profile 2191 with Loox LED 2068



- > CRI 90 lights are Title 24 compliant
- > CRI 90 lights offer more vibrant, true color rendering than lower CRI products
- > Life time: 30,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars see page 70

5 12 V Loox5 12 V driver see page 130

Note
Loox lights and drivers are "Suitable for use within closet storage spaces"

Components

- > Profile: 2191 - see page 36.
- > LED strip: 2068 - see page 10.
- > Mounting brackets: see page 36.
- > Lead cables: 100 mm (4") male and female

3000 K	4000 K	120°	
2250 lx	2300 lx		250 mm (9 13/16")
940 lx	950 lx		500 mm (19 11/16")
505 lx	510 lx		750 mm (29 1/2")
310 lx	320 lx		1000 mm (39 3/8")

Light Color (K)	3000 (warm white)				4000 (cool white)			
	101				104			
Lumen per watt	101				104			
Item No.	833.88.700	833.88.701	833.88.702	833.88.703	833.88.714	833.88.715	833.88.716	833.88.717
Length	152 (6")	229 (9")	305 (12")	381 (15")	152 (6")	229 (9")	305 (12")	381 (15")
Wattage	1.0	1.7	2.4	3.1	1.0	1.7	2.4	3.1
LEDs	12	21	30	39	12	21	30	39
Lumen	97	170	243	315	100	175	250	325
Item No.	833.88.704	833.88.705	833.88.706	833.88.707	833.88.718	833.88.719	833.88.720	833.88.721
Length	457 (18")	533 (21")	610 (24")	686 (27")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	3.8	4.6	5.3	6.0	3.8	4.6	5.3	6.0
LEDs	48	57	66	75	48	57	66	75
Lumen	388	461	534	606	400	475	550	625
Item No.	833.88.708	833.88.709	833.88.710	833.88.711	833.88.722	833.88.723	833.88.724	833.88.725
Length	762 (30")	832 (33")	915 (36")	991 (39")	762 (30")	832 (33")	915 (36")	991 (39")
Wattage	6.7	7.4	8.2	8.9	6.7	7.4	8.2	8.9
LEDs	84	93	102	111	84	93	102	111
Lumen	679	752	825	897	700	775	850	925
Item No.	833.88.712		833.88.713		833.88.726		833.88.727	
Length	1067 (42")		1143 (45")		1067 (42")		1143 (45")	
Wattage	9.6		10.3		9.6		10.3	
LEDs	120		129		120		129	
Lumen	970		1043		1000		1075	
CRI	90*							
Material	Aluminum; Lens: Plastic, opal							
Supplied with	100 mm (4") male mini driver cable, 100 mm (4") female mini driver cable, mounting brackets							

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.