


Surface mounted light bars

With linkable cable, 24 V

Profile 2103 with Loox LED 3087 multi-white 2-wire



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 131A–131B



Note

Loox lights and drivers are "Suitable for use within closet storage spaces"

Components

- > Profile: 2103 - see page 34.
- > Mounting brackets: see page 35.
- > Lead cable: 100 mm (4") male and female

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	Multi-white 2700-5000							
Item No.	833.88.900	833.88.901	833.88.902	833.88.903	833.88.904	833.88.905	833.88.906	833.88.907
Length	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")	762 (30")
Wattage	1.7	2.9	3.2	3.9	4.6	5.8	6.1	7.3
LEDs	21	30	39	48	57	66	75	84
Item No.	833.88.908	833.88.909	833.88.910	833.88.911	833.88.912	–	–	–
Length	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	–	–	–
Wattage	7.6	8.8	9	10.2	10.5	–	–	–
LEDs	93	102	111	120	129	–	–	–
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							

Material/Finish: Aluminum, black; Lens: Plastic, opal

Light Color (K)	Multi-white 2700-5000							
Item No.	833.88.919	833.88.920	833.88.921	833.88.922	833.88.923	833.88.924	833.88.925	833.88.926
Length	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")	762 (30")
Wattage	1.7	2.9	3.2	3.9	4.6	5.8	6.1	7.3
LEDs	21	30	39	48	57	66	75	84
Item No.	833.88.927	833.88.928	833.88.929	833.88.930	833.88.931	–	–	–
Length	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	–	–	–
Wattage	7.6	8.8	9	10.2	10.5	–	–	–
LEDs	93	102	111	120	129	–	–	–
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							