


# Surface mounted light bars

With linkable cable, 24 V

## Profile 2103 with Loox LED 3045



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 131A–131B



### Note

Loox lights and drivers are "Suitable for use within closet storage spaces"

### Components

- > Profile: 2103 - see page 34.
- > LED strip: 3045 - see page 13.
- > Mounting brackets: see page 35.
- > Lead cable: 100 mm (4") male and female

Material/Finish: Aluminum, silver; Lens: Plastic, opal

| Light Color (K) | 3000  |            |            |            |            |            |            |            |
|-----------------|---|------------|------------|------------|------------|------------|------------|------------|
| Item No.        | 833.70.885  | 833.70.886 | 833.70.887 | 833.70.888 | 833.70.889 | 833.70.890 | 833.70.891 | 833.70.892 |
| Length          | 152 (6")  | 229 (9")   | 305 (12")  | 381 (15")  | 457 (18")  | 533 (21")  | 610 (24")  | 686 (27")  |
| Wattage         | 1.0   | 1.7        | 2.9        | 3.2        | 3.9        | 4.6        | 5.8        | 6.1        |
| LEDs            | 12  | 21         | 30         | 39         | 48         | 57         | 66         | 75         |
| Item No.        | 833.70.893  | 833.70.894 | 833.70.895 | 833.70.896 | 833.70.897 | 833.70.898 |            |            |
| Length          | 762 (30")   | 832 (33")  | 915 (36")  | 991 (39")  | 1067 (42") | 1143 (45") |            |            |
| Wattage         | 7.3   | 7.6        | 8.8        | 9.0        | 10.2       | 10.5       |            |            |
| LEDs            | 84  | 93         | 102        | 111        | 120        | 129        |            |            |
| CRI             | >90   |            |            |            |            |            |            |            |
| Supplied with   | 100 mm (4") male lead, 100 mm (4") female lead, mounting brackets |            |            |            |            |            |            |            |

Material/Finish: Aluminum, silver; Lens: Plastic, opal

| Light Color (K) | 4000  |            |            |            |            |            |            |            |
|-----------------|---|------------|------------|------------|------------|------------|------------|------------|
| Item No.        | 833.70.899  | 833.70.900 | 833.70.901 | 833.70.902 | 833.70.903 | 833.70.904 | 833.70.905 | 833.70.906 |
| Length          | 152 (6")  | 229 (9")   | 305 (12")  | 381 (15")  | 457 (18")  | 533 (21")  | 610 (24")  | 686 (27")  |
| Wattage         | 1.0   | 1.7        | 2.9        | 3.2        | 3.9        | 4.6        | 5.8        | 6.1        |
| LEDs            | 12  | 21         | 30         | 39         | 48         | 57         | 66         | 75         |
| Item No.        | 833.70.907  | 833.70.908 | 833.70.909 | 833.70.910 | 833.70.911 | 833.70.912 |            |            |
| Length          | 762 (30")   | 832 (33")  | 915 (36")  | 991 (39")  | 1067 (42") | 1143 (45") |            |            |
| Wattage         | 7.3   | 7.6        | 8.8        | 9.0        | 10.2       | 10.5       |            |            |
| LEDs            | 84  | 93         | 102        | 111        | 120        | 129        |            |            |
| CRI             | >90   |            |            |            |            |            |            |            |
| Supplied with   | 100 mm (4") male lead, 100 mm (4") female lead, mounting brackets |            |            |            |            |            |            |            |