


## Surface mounted light bars

With linkable cable, 24 V

### Profile 2103 with Loox LED 3045



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 131A–131B



#### Note

Loox lights and drivers are "Suitable for use within closet storage spaces"

#### Components

- > Profile: 2103 - see page 34.
- > LED strip: 3045 - see page 13.
- > Mounting brackets: see page 35.
- > Lead cable: 100 mm (4") male and female

Material/Finish: Aluminum, black; Lens: Plastic, opal

Light Color (K)	3000							
<b>Item No.</b>	<b>833.70.913</b>	<b>833.70.914</b>	<b>833.70.915</b>	<b>833.70.916</b>	<b>833.70.917</b>	<b>833.70.918</b>	<b>833.70.919</b>	<b>833.70.920</b>
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
<b>Item No.</b>	<b>833.70.921</b>	<b>833.70.922</b>	<b>833.70.923</b>	<b>833.70.924</b>	<b>833.70.925</b>	<b>833.70.926</b>		
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")		
Wattage	7.3	7.6	8.8	9.0	10.2	10.5		
LEDs	84	93	102	111	120	129		
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							

Material/Finish: Aluminum, black; Lens; Plastic, opal

Light Color (K)	4000							
<b>Item No.</b>	<b>833.70.927</b>	<b>833.70.928</b>	<b>833.70.929</b>	<b>833.70.930</b>	<b>833.70.931</b>	<b>833.70.932</b>	<b>833.70.933</b>	<b>833.70.934</b>
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
<b>Item No.</b>	<b>833.70.935</b>	<b>833.70.936</b>	<b>833.70.937</b>	<b>833.70.938</b>	<b>833.70.939</b>	<b>833.70.940</b>		
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")		
Wattage	7.3	7.6	8.8	9.0	10.2	10.5		
LEDs	84	93	102	111	120	129		
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.