


# Surface mounted light bars

With inline switch, 24 V

## Profile 2103 with Loox LED 3045



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 131A–131B



### Note

Loox lights and drivers are "Suitable for use within closet storage spaces"

### Components

- > Profile: 2103 - see page 34.
- > LED strip: 3045 - see page 13.
- > Mounting brackets: see page 35.
- > Lead cable: 100 mm (4") male and female 833.89.291

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	3000							
Item No.	833.70.941	833.70.942	833.70.943	833.70.944	833.70.945	833.70.946	833.70.947	833.70.948
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.70.949	833.70.950	833.70.951	833.70.952	833.70.953	833.70.954		
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")		
Wattage	7.3	7.6	8.8	9.0	10.2	10.5		
LEDs	84	93	102	111	120	129		
CRI	>90							
Supplied with	2 m (78 3/4") modular lead, inline touch dimmer switch, 100 mm (4") female lead, mounting brackets							

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	4000							
Item No.	833.70.955	833.70.956	833.70.957	833.70.958	833.70.959	833.70.960	833.70.961	833.70.962
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.70.963	833.70.964	833.70.965	833.70.966	833.70.967	833.70.968		
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")		
Wattage	7.3	7.6	8.8	9.0	10.2	10.5		
LEDs	84	93	102	111	120	129		
CRI	>90							
Supplied with	2 m (78 3/4") modular lead, inline touch dimmer switch, 100 mm (4") female lead, mounting brackets							