

# LOOX LED DRIVER

CONSTANT VOLTAGE 12 V

**REALLY FLAT**

**12 V SYSTEM**

**1** Item No. 833.74.900  
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 15 \text{ W}$

**2** Item No. 833.74.917  
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 20 \text{ W}$

**3** Item No. 833.74.901  
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 30 \text{ W}$

**4** Item No. 833.74.913  
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 60 \text{ W}$

Parallel connection

The driver is the heart of the Loox system, and is suitable for connecting to all of the most popular power systems that are used around the world. It has an integrated switching function and connections for all of the most popular types of switch.

**!** > Lead length from driver to switch max. 6 m (20').

Item No.	833.74.900 <b>1</b>	833.74.917 <b>2</b>	833.74.901 <b>3</b>	833.74.913 <b>4</b>
SRP	\$36.00	\$36.00	\$60.00	\$72.00
Wattage (W)	0 – 15	0 – 20	0 – 30	0 – 60
Input voltage	100 – 240 V; 50 – 60 Hz			
Output voltage	DC 12 V			
Output current	1.25 A	1.67 A	2.5 A	5 A
Degree of protection	IP20			
Number of slots	6 slots for 12 V lights, 1 slot for switch, 1 slot for country-specific primary lead			
Material/Color	Plastic, black			
Length	140 (5 1/2")	128 (5 1/16")	195 (7 11/16")	208 (8 3/16")
Width	43 (1 11/16")	50.5 (2")	43 (1 11/16")	56.5 (2 1/4")
Height	20 (13/16")	14 (9/16")	28 (1 1/8")	30 (1 3/16")
Supplied with	Mounting accessories, US power cord			

Country-specific primary leads – 2 m (78 3/4")									3 m (118")
Item No.	833.89.000	833.89.001	833.89.002	833.89.003	833.89.004	833.89.005	833.89.006	833.89.050	833.89.008
SRP	\$9.10	\$4.00	\$4.00	\$4.00	\$4.00	\$4.00	\$4.00	\$4.00	\$6.00
Plug design									
Designation	UK	AU	EU	US	JP	CN	KR	US	US

**Note** Loox Lights and Drivers are "Suitable for use within Closet Storage Spaces"