



NOTES:

- 1 HORIZONTAL ADJUSTMENT:
 - 1.1. DISTANCE MUST BE 38.0 MAX WHEN FULLY ADJUSTED LEFT.
 - 1.2. DISTANCE MUST BE 41.8 MIN WHEN FULLY ADJUSTED RIGHT.
- 2 LATCH:
 - 2.1. FREE DISTANCE MUST BE MEASURED AS SHOWN.
 - 2.2. LATCH MUST MOVE 4.0 MIN, WHEN LEVER IS ACTUATED.

	ITEM#: US-CLIP-4W		MATERIAL: ---
	FINISH: ---		WEIGHT: g
	PROPRIETARY / CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HARDWARE RESOURCES INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HARDWARE RESOURCES INC. IS PROHIBITED.		PROJECTION
			TOLERANCE UNLESS OTHERWISE SPECIFIED: 0 < x < 6.29 ± 0.05 6.30 < x < 12.69 ± 0.10 12.70 < x < 25.39 ± 0.15 25.40 < x ± 0.25 ANGULAR: ±0.5°
DO NOT SCALE DRAWING	UNITS: mm SIZE: A4 SHEET: 1 OF 1	DRAWN BY: DENNIS MCGREGOR APPROVED BY: RELEASE LEVEL: In Work	DATE: 21MAR14 DATE: REVISION: 1.4