


**MOUNTING HOLE
DETAIL**

NOTES:

1. THE ANSI Z358.1-2009 STANDARD SPECIFIES EYEWASH NOZZLE HEIGHTS TO BE 83.8cm (33 IN.) TO 114.3cm (45 IN.) ABOVE THE FLOOR. CENTERLINE OF EYEWASH HEADS MUST BE 15.2cm (6 IN.) MIN. AWAY FROM WALL OR NEAREST OBSTRUCTION.
2. INSTALL SO THAT EYEWASH HEAD IS OVER SINK WHEN ACTIVATED.
3. DIMENSIONS MAY VARY BY ±1/2" [12.7mm]



1455 KLEPPE LANE
SPARKS, NEVADA 89431
(775) 359-4712 FAX (775) 359-7424
E-MAIL: HAWS@HAWSCO.COM
WEBSITE: WWW.HAWSCO.COM

ECN NO. REVISED PER BY:	ECN: 5005	HM	MODEL(S)
DRAWN:	DATE:	CHKD.:	7612
C. HAYES	05/07/91	RVH	
APPROVED:	DATE:		PART NUMBER
FV	08/25/15		0002080064.D
			REVISION
			12
		SCALE: 1:1	DRAWING TYPE: INSTALLATION
			SIZE: A SHEET 1 OF 1