



model 7602.15
Portable Units

FEATURES & BENEFITS

CONSTRUCTION

Stainless steel constructed tank makes for a solid portable unit with added resistance against corrosion and breakage.

VALVES

Valve comes equipped with stainless steel ball and stem for added protection against corrosion and breakage. Full continuous flow occurs with the simple push of a stainless steel flag.

ADDED PROTECTION/MISC.

Green polyethylene plastic dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation.

SAFETY

Air pressure gauge, pressure relief valve, tire-type air fill valve, and supplied bottle of bacteriostatic additive decrease the possibility of mishaps and make for a safer piece of emergency equipment.

FLOW CONTROLS

Green ABS plastic Soft-Flo anti-surge heads distribute water at a rate of .25 gpm when pressure is between 30 and 90 psi. Combine this with capabilities of a 15 gallon portable and the irrigation process is a thorough one.



SPECIFICATIONS

Model 7602.15, pressurized portable emergency eyewash shall include 15 gallon stainless steel container equipped with pressure gauge and safety relief valve, Soft-Flo™ ABS plastic eyewash anti-surge heads with .25 gpm flow controls and dust covers, chrome plated brass stay-open 1/2" IPS eyewash valve with stainless steel ball and valve stem, with large stainless push handle activation.

OPTIONS

- ❑ Hose & Spray Unit: Model 8901B, wall-mounted body spray with 8-foot pressure rated hose, including wall mounting bracket.
- ❑ Cart: Model 9007 cart designed to transport all 10 through 15 gallon portable eyewashes, 7500 or 7501 series, and 9009 wastewater container. Unit is constructed of heavy-duty 1" tubular frame with green powder-coated finish and comes equipped with four solid rubber wheels.
- ❑ Bacteriostatic Additive: Model 9082, bacteriostatic preservative for use in portable eyewash stations. One 8 oz. (237 ml) bottle will preserve 6 to 20 gallons of portable water for up to six months. Four bottles per carton.

To see all options for this model, visit www.hawesco.com

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, when suitable facilities for quick flushing of the eyes needs to be provided and a continuous supply of water is not available. Although the 7602.15 may be used in a wide variety of locations, it is ideal for the remote and low traffic areas where protective and mobile measures may still be needed. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7602.15 is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.