



DORIAN 2192BZ-LED	
BRONZE	

WIDTH: 6.0" HEIGHT: 18.3" WEIGHT: 7.0 LBS MATERIAL: ALUMINUM GLASS: CLEAR PAINTED WHITE INSIDE CANOPY: 5.5" DIA. SOCKET: 30W LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED CEILING 90°			
WEIGHT: 7.0 LBS MATERIAL: ALUMINUM GLASS: CLEAR PAINTED WHITE INSIDE CANOPY: 5.5" DIA. SOCKET: 30W LED INCLUDED LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	WIDTH:	6.0"	
MATERIAL: GLASS: CLEAR PAINTED WHITE INSIDE CANOPY: 5.5" DIA. SOCKET: 30W LED *INCLUDED LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 1NSTALL OPTIONS: UP, INSTALL ON SLOPED	HEIGHT:	18.3"	
GLASS: CLEAR PAINTED WHITE INSIDE CANOPY: 5.5" DIA. SOCKET: 30W LED **INCLUDED LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	WEIGHT:	7.0 LBS	
INSIDE CANOPY: 5.5" DIA. SOCKET: 30W LED *INCLUDED LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT 2 x 100W EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	MATERIAL:	ALUMINUM	
SOCKET: 30W LED *INCLUDED LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT 2 x 100W EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	GLASS:	022,	
*INCLUDED LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT 2 x 100W EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	CANOPY:	5.5" DIA.	
LED INFO: LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: 2 x 100W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	SOCKET:	30W LED	
LUMENS: 2400 COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: 2 x 100W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED		*INCLUDED	
COLOR TEMP: 3000k CRI: 96 INCANDESCENT EQUIVALENCY: 2 x 100W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	LED INFO:		
CRI: 96 INCANDESCENT EQUIVALENCY: 2 x 100W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	LUMENS:	2400	
INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	COLOR TEMP:	3000k	
EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	CRI:	96	
MLV, ELV, or C-L dimmer. LEADWIRE: 72.0" CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED		2 x 100W	
CERTIFICATION: C-US DAMP RATED VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	DIMMABLE:		
VOLTAGE: 120V UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	LEADWIRE:	72.0"	
UPC: 640665219241 INSTALL OPTIONS: UP, INSTALL ON SLOPED	CERTIFICATION:	C-US DAMP RATED	
INSTALL OPTIONS: UP, INSTALL ON SLOPED	VOLTAGE:	120V	
	UPC:	640665219241	
	INSTALL OPTIONS:		

AT HINKLEY, WE EMBRACE THE DESIGN PHILOSOPHY THAT YOU CAN MERGE TOGETHER THE LIGHTING, FURNITURE, ART, COLORS AND ACCESSORIES YOU LOVE INTO A BEAUTIFUL ENVIRONMENT THAT DEFINES YOUR OWN PERSONAL STYLE. WE HOPE YOU WILL BE INSPIRED BY OUR COMMITMENT TO KEEP YOUR 'LIFE AGLOW.'

life AGLOW®