

HINKLEY LIGHTING, INC.
33000 PIN OAK PARKWAY | AVON LAKE, OHIO 44012
[PH] 440.653.5500 [F] 440.653.5555
HINKLEYLIGHTING.COM | FREDRICKRAMOND.COM



HORIZON 2895BK	
BLACK	

WIDTH: 5.3" HEIGHT: 20.5" WEIGHT: 3.5 LBS MATERIAL: ALUMINUM GLASS: CLEAR SEEDY BACKPLATE WIDTH: 5.0" BACKPLATE HEIGHT: 4.5" SOCKET: 16W LED INCLUDED LED INFO: LUMENS: LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: 1 x 75W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503 INSTALL OPTIONS: UP AND VERTICALLY			
WEIGHT: 3.5 LBS MATERIAL: ALUMINUM GLASS: CLEAR SEEDY BACKPLATE WIDTH: 5.0" BACKPLATE HEIGHT: 4.5" SOCKET: 16W LED INCLUDED LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	WIDTH:	5.3"	
MATERIAL: ALUMINUM GLASS: CLEAR SEEDY BACKPLATE WIDTH: 5.0" BACKPLATE HEIGHT: 4.5" SOCKET: 16W LED INCLUDED LED INFO: LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	HEIGHT:	20.5"	
GLASS: CLEAR SEEDY BACKPLATE WIDTH: 5.0" BACKPLATE HEIGHT: 4.5" SOCKET: 16W LED INFO: LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: 1 x 75W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	WEIGHT:	3.5 LBS	
BACKPLATE WIDTH: BACKPLATE HEIGHT: SOCKET: 16W LED INCLUDED LED INFO: LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	MATERIAL:	ALUMINUM	
WIDTH: BACKPLATE HEIGHT: SOCKET: 16W LED *INCLUDED LED INFO: LUMENS: 800 COLOR TEMP: 2700k CRI: INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	GLASS:	CLEAR SEEDY	
HEIGHT: SOCKET: 16W LED *INCLUDED		5.0"	
*INCLUDED		4.5"	
LUMENS: 800 COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: 1 x 75W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	SOCKET:		
COLOR TEMP: 2700k CRI: 91 INCANDESCENT EQUIVALENCY: 1 x 75W DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	LED INFO:		
CRI: INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	LUMENS:	800	
INCANDESCENT EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	COLOR TEMP:	2700k	
EQUIVALENCY: DIMMABLE: Yes, on any Incandescent, MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	CRI:	91	
MLV, ELV, or C-L dimmer. NOTES: MULTIPLE TOP TO OUTLET MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503		1 x 75W	
MEASUREMENTS WITH ADJUSTABLE GLASS POSITIONING. EXTENSION: 3.8" TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	DIMMABLE:		
TTO: 10.3" CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	NOTES:	MEASUREMENTS WITH ADJUSTABLE GLASS	
CERTIFICATION: C-US WET RATED VOLTAGE: 120V UPC: 640665289503	EXTENSION:	3.8"	
VOLTAGE: 120V UPC: 640665289503	TTO:	10.3"	
UPC: 640665289503	CERTIFICATION:	C-US WET RATED	
	VOLTAGE:	120V	
INSTALL OPTIONS: UP AND VERTICALLY	UPC:	640665289503	
	INSTALL OPTIONS:	UP AND VERTICALLY	

AT HINKLEY, WE EMBRACE THE DESIGN PHILOSOPHY THAT YOU CAN MERGE TOGETHER THE LIGHTING, FURNITURE, ART, COLORS AND ACCESSORIES YOU LOVE INTO A BEAUTIFUL ENVIRONMENT THAT DEFINES YOUR OWN PERSONAL STYLE. WE HOPE YOU WILL BE INSPIRED BY OUR COMMITMENT TO KEEP YOUR 'LIFE AGLOW.'