

PRODUCT DETAILS:

- Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Three lens options included offer versatility in beam spread via an easy to remove and insert optic assembly.
- Lamp adjustable +/- 20 degrees
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve is supplied.
- Includes a dense foam cap to prevent concrete from entering

FLAT TOP WELL LIGHT 120V

55702BZ27K

LED 12W 2700K FLAT TOP WELL LIGHT

DETAILS	
FINISH:	Bronze

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
WEIGHT:	4.5 lbs.

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	27G3SE-120V-75
WATTAGE:	12w LED *Included
VOLTAGE:	120v
COLOR TEMP:	2700.0000k
LUMENS:	749
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 75W

MOUNTING	
LEAD WIRE:	96"

SHIPPING	
CARTON LENGTH:	7"
CARTON WIDTH:	7"
CARTON HEIGHT:	13.5"
CARTON WEIGHT:	4.5 lbs.



Toll Free: 1 (800) 446-5539