PERIMALITER®
WALLPACK

Cat. #	Approvals	
Job	Туре	



D

613/16"

173 mm

В

15"

381 mm

8"

203 mm

PGM3

147/8"

378 mm

APPLICATIONS

PGM3 GLASS SERIES

· Perimeter lighting for safety and security. High performance with wide lateral spread.

SPECIFICATIONS

- Cast aluminum door frame with prismatic glass refractor. Door seals to housing gasket with twin Hubbell Gard® captive fasteners.
- Die cast aluminum housing allows firm mounting over recessed junction boxes or on flat surfaces for 1/2" surface conduit. Casting dissipates ballast heat for long life. Top hub supplied for field installation of button photo control, ordered separately.
- Specular aluminum reflector with kicker panels drive maximum lamp lumens to the refractor prisms. Vertical socket position with these optics provide six to one spacing to mounting height ratio for maximum spacing or better uniformity, greater lumens and lamp life.
- PGM features 70-250w HPS and pulse start metal halide. QuadTap®, 347V and 50Hz 220/240V available. Many listings include lamp for contractor convenience; see standard selections
- Dark bronze 800 Series powder paint finish standard on frame and housing. For optional finishes, black, gray, white and platinum consult factory.






LISTINGS

CSA certified to UL 1598 for use in wet locations.

ORDERING INFORMATION

ORDERING EXAMPLE: PGM3-150P-18-BZ-EM-L



Catalog Number	Wattage	Source	Voltage	Ballast	Lamp Included	We	ight
						lbs.	kg
		PULSE STAR	T METAL HALIDE				
PGM3-070P-18-BZ-L	70	PS	Quad Tap	HX-HPF	Yes	24	10.9
PGM3-100P-18-BZ-L	100	PS	Quad Tap	HX-HPF	Yes	25	11.3
PGM3-150P-18-BZ-L	150	PS	Quad Tap	HX-HPF	Yes	25	11.3
PGM3-250P-18-BZ-L	250	PS	Quad Tap	CWA-HPF	Yes	27	12.2
		HIGH PRES	SURE SODIUM				
PGM3-070S-18-BZ	70	HPS	Quad Tap	AL-HPF	No	23	10.4
PGM3-100S-18-BZ	100	HPS	Quad Tap	AL-HPF	No	24	10.9
PGM3-150S-18-BZ	150	HPS	Quad Tap	AL-HPF	No	25	11.3
PGM3-150S-18-BZ-L	150	HPS	Quad Tap	AL-HPF	Yes	25	11.3
PGM3-250S-18-BZ	250	HPS	Quad Tap	CWA-HPF	No	30	13.6
PGM3-250S-18-BZ-L	250	HPS	Quad Tap	CWA-HPF	Yes	33	14.9
		LESS	BALLAST				
PGM3-LB [†]	250 Max	None	None	None	No	15	6.8

L Indicates lamp included with the fixture.

L minicates ramp included with use instance.

Above units (-18) are Quad Tap (120,208,240,277V. 480V available on 150w units change 8 to 5.

For TriTap Canadian ballast (120,277,347V) change 8 to 6.

BZ - Dark Bronze finish is standard. For alternate finish - consult factory for price adder and availability

Finishes available with adder: BL- Black, GR- Gray, WH- White, PS - Platinum

50HZ ballastry is available - Consult factor

BZ Replacement Lens/Door is 800 3399 0104

*Socket is mogul base/finish is bronze

ACCESSORIES (order as separate part #)

	Catalog Number
	PBT-1
	PBT-234
	PG-PS ¹
	PG-WG¹
	PVL3V
_	

OPTIONS

(factory installed, add appropriate suffix)

Catalog Number	Description	
-EM	Double Contact Socket for remote power (less lamp) all units	
-QSS	Quartz Restrike System including relay (less lamp) all units	
	(double contact bayonet socket)	
-RS	Hot Restrike System, quickly restores main lamp output after	
	power outage (HPS only), 150w maximum.	
-L	Lamp included with fixture	

HUBBELL OUTDOOR LIGHTING SHEET # PGM/PGL-SPEC7/10

PHOTOMETRIC REPORTS

Catalog Number	Report #
PGM-150S	HP07246.IES
PGM-250S	HP07358.IES
PGM3-100P	HP2383.IES
PGM3-250P With/PVL3V	HP2427.IES

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Hubbell Outdoor Lighting ● 701 Millennium Boulevard ● Greenville, SC 29607 ● PHONE: 864-678-1000

For more information visit our web site: www.hubbell-ltg.com